

Variable Length Argument Lists

- Functions that take a variable number of arguments

```
int sum(int x, ...) { ... }
there must be at least one named formal parameter
```

- `stdarg.h` defines types, macros, and functions to deal with variable arguments

```
va_list      the type of a "pointer to a variable argument list"
va_start(va_list ap, last)
    initializes ap for the list that follows the formal parameter last
    va_start must be called before any calls to va_arg

type va_arg(ap, type)
    returns the next argument, which must have datatype type
    adjusts ap to point the next variable argument

void va_end(va_list ap)
    called after all of the arguments have been processed
```

- No way to determine the number of actual arguments

the necessary information must be encoded in the values of the arguments
e.g., `printf` format codes

Example: Macros for Variable Length Argument Lists

- `int sum(int x, ...)` returns the sum of its non-zero integer arguments

<code>sum(0)</code>	0
<code>sum(1, 2, 3, 0)</code>	6
<code>sum(-1, 2, 3, -4, 0)</code>	0

- Implementation

```
#include <stdarg.h>

int sum(int x, ...) {
    va_list ap;
    int n = 0;

    va_start(ap, x);
    while (x) {
        n += x;
        x = va_arg(ap, int);
    }
    va_end(ap);
    return n;
}
```

printf-Style Functions

- Use `stdarg.h` to implement special-purpose `printf`-style functions

```
#include <stdarg.h>
#include <stdlib.h>
#include <stdio.h>

void error(char *fmt, ...) {
    va_list ap;

    va_start(ap, fmt);
    fprintf(stderr, "error: ");
    for ( ; *fmt; fmt++)
        if (*fmt == '%')
            switch (*++fmt) {
                case 'd': fprintf(stderr, "%d", va_arg(ap, int)); break;
                case 's': fprintf(stderr, "%s", va_arg(ap, char *)); break;
                ...
                case 'N': fprintf(stderr, "at line %d", lineno); break;
                default: fputc(*fmt, stderr); break;
            }
        else
            fputc(*fmt, stderr);
    va_end(ap);
    fprintf(stderr, "\n");
    exit(EXIT_FAILURE);
}
```

Library printf-Style Functions

- Some standard library functions take `va_list` values

```
#include <assert.h>
#include <stdarg.h>
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

void error(char *fmt, ...) {
    va_list ap;
    va_start(ap, fmt);
    fprintf(stderr, "error: ");
    vfprintf(stderr, fmt, ap);
    va_end(ap);
    fprintf(stderr, "\n");
    exit(EXIT_FAILURE);
}

char *stringf(char *fmt, ...) {
    va_list ap;
    char *s, buf[512];
    va_start(ap, fmt);
    vsprintf(buf, fmt, ap);
    va_end(ap);
    s = malloc(strlen(buf) + 1);
    assert(s);
    return strcpy(s, buf);
}
```