Arithmetic Operators

- "Normal" binary arithmetic operators: **`+ - * /`**
- Modulus or remainder operator: %

  `x%y` is the remainder when **`x`** is divided by **`y`**

  well defined ***only*** when **`x > 0`** and **`y > 0`**
- Unary operators: **`- +`**
- Precedence (see K&R, section 2.12)

  highest unary **`- +`**

  `* /` %

  lowest **`+ -`**

  so **`-2*a + b`** is parsed as **`(((-2)*a) + b)`**
- Associativity: left to right

  `a + b + c` is parsed as **`((a + b) + c)`**

Portability: Printing Numbers

- Print a number in decimal

```
void putd(int n) {
    if (n < 0) {
        putchar('-');
        n = -n;
    }
    if (n >= 10)
        putd(n/10);
    putchar(n%10 + '0');
}
```

- Can this program print **`INT_MIN == -2147483648?`**

Portability: Printing Numbers, Con'd

- Convert negative numbers

```
static void putneg(int n) {
    if (n <= -10)
        putneg(n/10);
    putchar("0123456789"[-(n%10)]);
}

void putd(int n) {
    if (n < 0) {
        putchar('-');
        putneg(n);
    } else
        putneg(-n);
}
```

- **`n/10`** and **`n%10`** are "implementation dependent" when **`n < 0`**

Portability, cont'd

- Remainder is a mess:

```
int a, b, q, r;
q = a/b; r = a%b;
```

ANSI Standard guarantees *only*

```
q*b + r == a
|r| < |b|
r >= 0 when a >= 0 && b > 0
```

`r` *might* be negative if `a` is

`5/(-3) = -1.666...`



if **`5/(-3) == -2`**,
`5%(-3) = 5 - (-2)(-3) = -1`

if **`5/(-3) == -1`**,
`5%(-3) = 5 - (-1)(-3) = 2`

- Check for sign of `n%10`, handle both

```
static void putneg(int n) {
    int q = n/10, r = n%10;

    if (r > 0) {
        r -= 10;
        q++;
    }
    if (n <= -10)
        putneg(q);
    putchar("0123456789"[-r]);
}
```

if **`(-7)/10 == -1`**,
`(-7)%10 = -7 - (-1)(10) = 3`

if **`(-7)/10 == 0`**,
`(-7)%10 = -7 - (0)(10) = -7`

An Easier Way

- Use unsigned arithmetic

```
#include <limits.h>
#include <stdio.h>

static void putu(unsigned n) {
    if (n > 10)
        putu(n/10);
    putchar("0123456789"[n%10]);
}

void putd(int n) {
    if (n == INT_MIN) {
        putchar('-');
        putu((unsigned)INT_MAX + 1);
    } else if (n < 0) {
        putchar('-');
        putu(-n);
    } else
        putu(n);
}
```

Copyright ©1995, 1996. D. Hanson, K. Li, A. Rogers, J.P. Singh

Increment/Decrement

- ***Prefix*** operator increments operand ***before*** returning the value

```
n = 5;
x = ++n;
```

  x is **6**, **n** is **6**

- ***Postfix*** operator increments operand ***after*** returning the value

```
n = 5;
x = n++;
```

  x is **5**, **n** is **6**

- Operands of **++** and **--** must be ***variables***

```
++1
2 + 3++
```

  are illegal

Copyright ©1995, 1996. D. Hanson, K. Li, A. Rogers, J.P. Singh

Relational & Logical Operators

- Logical values are integers: 0 is false, !0 is true
- "Normal" relational operators: **> >= < <=**
- Equality operators: **== !=**
- Unary logical negation: **!**
- Logical connectives: **&& ||**

  Evaluation rules: left-to-right ; ***as far as*** needed to determine the outcome

  && stops when the outcome is known to be 0

  || stops when the outcome is known to be !0

```
if (i >= 0 && i < 10 && a[i] == max)
    ++a[i];
```

- Associativity: left to right; precedence:

highest	**!**
	arithmetic operators
	< <= >= >
	== !=
	&&
lowest	**||**

Copyright ©1995, 1996. D. Hanson, K. Li, A. Rogers, J.P. Singh

Bit Manipulation

- Bitwise logical operators apply to all the bits of an integer value:

&	bitwise AND	**1&1=1**	**0&1=0**
|	bitwise inclusive OR	**1|0=1**	**0|0=0**
^	bitwise exclusive OR	**1^1=0**	**1^0=1**
unary **~**	bitwise complement	**~1=0**	**~0=1**

- The **|** operator can be used to "turn on" one or more bits

```
#define BIT0 0x1
#define BIT1 0x2
#define BITS (BIT0 | BIT1)
flags = flags | BIT0;
```

- the **&** operator can be used to "mask off" one or more bits

```
test = flags & BITS;
```

- examples using 16-bit quantities

```
BIT0 =          0000000000000001
BIT1 =          0000000000000010
BITS =          0000000000000011
flags =         0100011100000001
flags | BITS =  0100011100000011
flags & BITS =  0000000000000001
```

Copyright ©1995, 1996. D. Hanson, K. Li, A. Rogers, J.P. Singh

Shifting

- Shift operators: **`<< >>`**

  `x<<y` shifts **`x`** ***left*** **`y`** bit positions

  `x>>y` shifts **`x`** ***right*** **`y`** bit positions

- When shifting right:

  if **`x`** is signed, shift may be ***arithmetic*** or ***logical***

  if **`x`** is unsigned, shift is ***logical***

  arithmetic shift fills with ***sign bit***

  logical shift fills with 0

- When shifting left, the vacated bits are always filled with 0
- Examples using 16-bit quantities

```
bits =      1100011100000001
bits << 2 = 0001110000000100
bits >> 2 = 1111000111000000 (arithmetic, with sign extension)
bits >> 2 = 0011000111000000 (logical)
```

Copyright ©1995, 1996. D. Hanson, K. Li, A. Rogers, J.P. Singh

Assignment

- Assignment is an ***operator***, not a statement

```
c = getchar();
if (c == EOF) ...
```

can be written as

```
if ((c = getchar()) == EOF) ...
```

- Watch out for "typos" like

```
if (c = EOF) ...
```

probably meant `==`; power tools can maim...

- "Augmented" assignment combines **`+ - * / % >> << & ^ |`** with **`=`**

`i = i + 2`	is the same as	**`i += 2`**
`flags = flags | BIT0`		**`flags |= BIT0`**;
e_1 ***op***= e_2	is the same as	e_1 = e_1 ***op*** e_2
	except that e_1 is evaluated once	

- Watch out for precedence

`x *= y + 1` means **`x *= (y + 1)`**

not **`(x *= y) + 1`** (which is also legal)

Copyright ©1995, 1996. D. Hanson, K. Li, A. Rogers, J.P. Singh

Conversions

- ***Implicit*** conversions occur in expressions and across assignments
- **In expressions with mixed types, "Promote" to the "higher" type**

  `int + float` → **`float + float`**

  `short + long` → **`long + long`**

- Watch out for sign extension! e.g. **`char`** → **`int`**

```
char c = '\377'; int i = c;
```

is **`i`** equal to **`0377`** ***or*** **`-1`**? when in doubt, mask: **`i = c&0377`**

- Assigning a "big" **`int`** to a "small" **`int`**, causes the extra bits to be ***discarded***
- Assigning a **`float`** or **`double`** to an **`int`** ***truncates***

```
int n = 2.5
```

assigns `2` to `n`

- ***Explicit*** conversions are specified with ***casts***: (***type***)***expr***

```
sqrt((double)n)
(int)1.5
```

- study K&R, section 2.7 ***carefully***

Copyright ©1995, 1996. D. Hanson, K. Li, A. Rogers, J.P. Singh

Evaluation Order

- Except for **`&&`** and **`||`**, the evaluation order of expressions is ***undefined***;
- Avoid expressions whose outcome might depend on evaluation order

```
x = f() + g();
a[i] = i++;
f(++n, g(n));
```

use `lint`!

Operators	Associativity
`() [] -> .`	left to right
`! ~ ++ -- + - * & (`*`type`*`) sizeof`	right to left
`* / %`	left to right
`+ -`	left to right
`<< >>`	left to right
`< <= > >=`	left to right
`== !=`	left to right
`&`	left to right
`^`	left to right
`|`	left to right
`&&`	left to right
`||`	left to right
`?:`	right to left
`= += -= /= %= &= ^= |= <<= >>=`	right to left
`,`	left to right

Copyright ©1995, 1996. D. Hanson, K. Li, A. Rogers, J.P. Singh