

COS 597A, Fall 2008 -Problem Set 2

Due at 3:00pm Wednesday, October 8, 2008

Collaboration Policy

You may discuss problems with other students in the class. However, each student must write up his or her own solution to each problem independently. That is, while you may formulate the solutions to problems in collaboration with classmates, you must be able to articulate the solutions on your own.

Late Penalties

- 10% of the earned score if submitted after class but by 6:00pm the day due.
- 20% of the earned score if submitted by 5pm on Friday 10/10/08.
- 40% of the earned score if submitted by 5pm on Monday 10/13/08.
- **No credit** if submitted later than the 40% penalty deadline.

Chapter, exercise and page numbers refer to the course text *Database System Concepts, Fifth Edition*, by Silberschatz, Korth, and Sudarshan

1. (10 points)

Give an example of two relations R and Q and a tuple of R that is not in $(R \div Q) \times Q$. You must specify all the tuples in R and Q. It is fine for R and Q to be small, but $R \div Q$ must not be empty.

2. (20 points)

Part a: Let R be a relation with attributes (a,b,c,d) over domains A, B, C, and D, respectively. Let {a} and {b,c} be two candidate keys for R. Let {b} be a foreign key referencing attribute x, the primary key of relation X. Let Q be a relation with attributes (e,f,g,h) over domains A, B, C, and D, respectively. Let {g,h} be a candidate key for Q, and let {e,h} be a foreign key referencing attributes {y,z}, the primary key of relation Y. What candidate key and foreign key constraints *must* be true of R-Q?

Part b: Let R again be a relation with attributes (a,b,c,d) over domains A,B,C, and D, respectively. Again let {a} and {b,c} be two candidate keys for R, and let {b} be a foreign key referencing attribute x, the primary key of relation X. Let T be a relation with attributes (c,d) over domains C and D, respectively. Let {c} be a candidate key for T and let {d} be a foreign key referencing attribute u, the primary key of relation U. What candidate key and foreign key constraints *must* be true of $R \div T$?

3. (30 points)

For this problem we will use the following relational database (based on but *not identical to* Figure 2.35, pg 71 and Exercise 2.5, pg 72).

- relation *employee* with attributes (name, street, city)
- relation *company* with attributes (co_name, city)
- relation *works* with attributes (name, co_name, salary)
 - name is a foreign key referencing *employee*
- relation *manages* with attributes (employee_name, manager_name)
 - employee_name is a foreign key referencing *works*
 - manager_name is a foreign key referencing *works*

Express the following queries with relational algebra expressions. You may use any relational algebra operations, including intersection, join and division.

- i. Find the names of all employees who work for Microsoft and draw a salary of no more than \$30,000.
- ii. Find the names and employers' names of all employees who live in Trenton and draw a salary of more than \$1,000,000 per year.
- iii. Find the names of all companies that do not have a location in Princeton.
- iv. Assume companies may be located in several cities. Find the names of all companies located in every city in which Fred's Pizza Co. is located.
- v. Find the names and addresses of all employees who earn more than every manager of IBM.

4. (10 points)

Let R be a relation with attributes (a, b, c, d) where the domain of b is integers. For each relational calculus query below, state whether or not there is an equivalent relational algebra query. If you say there is, give the relational algebra query; if you say there is not, state why.

Part a: $\{T \mid T[b] < 100\}$

Part b: $\{T \mid (T \in R) \wedge (T[b] < 100)\}$

Part c: $\{T \mid \exists Q \in R ((Q[b] = T[b]) \wedge (T[b] < 100))\}$

5. (30 points) Express the queries of Problem 3 in the tuple relational calculus.