

Princeton University

COS 217: Introduction to Programming Systems

Heap Manager: Algorithms for First Assignment Implementation

```
void *HeapMgr_malloc(size_t uiBytes)
```

- (1) If this is the first call of `HeapMgr_malloc()`, then initialize the heap manager.
- (2) Determine the number of units the new chunk should contain.
- (3) For each chunk in the free list...

If the current free list chunk is big enough...

If the current free list chunk is close to the requested size, then remove it from the free list, set its status to `INUSE`, and return it. If the current free list chunk is too big, then remove it from the free list, split the chunk, insert the **tail** end of it into the free list, set the status of the **front** end of it to `INUSE`, set the status of the **tail** end of it to `FREE`, and return the **front** end of it.

- (4) Ask the OS for more memory – enough for the new chunk. Return `NULL` if the OS refuses. Create a new chunk using that memory. Insert the new chunk into the free list. If appropriate, coalesce the new chunk and the previous one in memory. To do so, remove both chunks from the free list, coalesce them to form a larger chunk, and insert the larger chunk into the free list. Let the current free list chunk be the new chunk.
- (5) If the current free list chunk is close to the requested size, then remove it from the free list, set its status to `INUSE`, and return it. If the current free list chunk is too big, then remove it from the free list, split the chunk, insert the **tail** end of it into the free list, set the status of the **front** end of it to `INUSE`, set the status of the **tail** end of it to `FREE`, and return the **front** end of it.

```
void HeapMgr_free(void *pvBytes)
```

- (1) Set the status of the given chunk to `FREE`.
- (2) Insert the given chunk into the free list.
- (3) If appropriate, coalesce the given chunk and the previous one in memory. To do so, remove both chunks from the free list, coalesce them to form a larger chunk, and insert the larger chunk into the free list.
- (4) If appropriate, coalesce the given chunk and the next one in memory. To do so, remove both chunks from the free list, coalesce them to form a larger chunk, and insert the larger chunk into the free list.