


## 3.2 Creating Data Types



### Data Types

**Data type.** Set of values and operations on those values.

**Basic types.**

Data Type	Set of Values	Some Operations
<code>boolean</code>	<code>true</code> , <code>false</code>	not, and, or, xor
<code>int</code>	$-2^{31}$ to $2^{31} - 1$	add, subtract, multiply
<code>String</code>	sequence of Unicode characters	concatenate, compare

**Last time.** Write programs that **use** data types.

**Today.** Write programs to **create** our own data types.

### Defining Data Types in Java

**To define a data type, define:**

- Set of values.
- Operations defined on them.

**Java class.** Allows us to define data types by specifying:

- **Instance variables.** (set of values)
- **Methods.** (operations defined on them)
- **Constructors.** (create and initialize new objects)

## Point Charge Data Type

**Goal.** Create a data type to manipulate point charges.

**Set of values.** Three real numbers. [position and electrical charge]


**Operations.**

- Create a new point charge at  $(r_x, r_y)$  with electric charge  $q$ .
- Determine electric potential  $V$  at  $(x, y)$  due to point charge.
- Convert to String.

$$V = k \frac{q}{r}$$

$r$  = distance between  $(x, y)$  and  $(r_x, r_y)$

$k$  = electrostatic constant  $\approx 8.99 \times 10^9 \text{ N} \cdot \text{m}^2 / \text{C}^2$



5

## Point Charge Data Type

**Goal.** Create a data type to manipulate point charges.

**Set of values.** Three real numbers. [position and electrical charge]

**API.**

public class Charge

---

Charge(double x0, double y0, double q0)	<i>electric potential at <math>(x, y)</math> due to charge</i>
double potentialAt(double x, double y)	<i>string representation</i>
String toString()	

6

## Charge Data Type: A Simple Client

**Client program.** Uses data type operations to calculate something.

```
public static void main(String[] args)
{
    double x = Double.parseDouble(args[0]);
    double y = Double.parseDouble(args[1]);
    Charge c1 = new Charge(.51, .63, 21.3);
    Charge c2 = new Charge(.13, .94, 81.9);
    double v1 = c1.potentialAt(x, y);
    double v2 = c2.potentialAt(x, y);
    StdOut.println(c1); ← automatically invokes
    StdOut.println(c2); ← the toString() method
    StdOut.println(v1 + v2);
}

% java Charge .50 .50
21.3 at (0.51, 0.63)
81.9 at (0.13, 0.94)
2.74936907085912e12
```

7

## Anatomy of Instance Variables

**Instance variables.** Specifies the set of values.

- Declare outside any method.
- Always use access modifier **private**.
- Use modifier **final** with instance variables that never change.


stay tuned

```
public class Charge
{
    private final double rx, ry;
    private final double q;
    ...
}
```

8

## Anatomy of a Constructor

**Constructor.** Specifies what happens when you create a new object.



**Invoking a constructor.** Use `new` operator to create a new object.

```


Charge c1 = new Charge(.51, .63, 21.3);
Charge c2 = new Charge(.13, .94, 81.9);
  
```

Annotations: `invoke constructor` points to the second line.

9

## Anatomy of a Data Type Method

**Method.** Define operations on instance variables.



**Invoking a method.** Use dot operator to invoke a method.


```

double v1 = c1.potentialAt(x, y);
double v2 = c2.potentialAt(x, y);
  
```

Annotations: `object name` (c1) and `invoke method` (potentialAt) are labeled.

10

## Anatomy of a Class



11


## Charge Client Example: Potential Visualization

**Potential visualization.** Read in N point charges from a file; compute total potential at each point in unit square.

```

more charges.txt
.51 .63 -100
.50 .50 40
.50 .72 10
.33 .33 5
.20 .20 -10
.70 .70 10
.82 .72 20
.85 .23 30
.90 .12 -50
  
```

```
% java Potential < charges.txt
```



12

## Potential Visualization

**Arrays of objects.** Allocate memory for the array; then allocate memory for each individual object.

```
// Read in the data.
int N = StdIn.readInt();
Charge[] a = new Charge[N];
for (int i = 0; i < N; i++)
{
    double x0 = StdIn.readDouble();
    double y0 = StdIn.readDouble();
    double q0 = StdIn.readDouble();
    a[i] = new Charge(x0, y0, q0);
}
```

## Potential Visualization

```
// Plot the data.
int SIZE = 512;
Picture pic = new Picture(SIZE, SIZE);
for (int row = 0; row < SIZE; row++)
    for (int col = 0; col < SIZE; col++)
    {
        double V = 0.0;
        for (int i = 0; i < N; i++)
        {
            double x = 1.0 * row / SIZE;
            double y = 1.0 * col / SIZE;
            V += a[i].potentialAt(x, y);
        }
        Color color = getColor(V); // Arbitrary double-Color map.
        pic.set(row, SIZE-1-col, color);
    }
pic.show();
```

$V = \sum_i (k q_i / r_i)$

(0, 0) is upper left

13

14


## TEQ on Data Types

[easy if you read Exercise 3.2.5]

Fix the serious bug in the following code.

```
public class Charge
{
    private double rx, ry;
    private double q;
    public Charge double x0, double y0, double q0)
    {
        double rx = x0;
        double ry = y0;
        double q = q0;
    }
}
```

## Turtle Graphics



15

## Turtle Graphics

**Goal.** Create a data type to manipulate a turtle moving in the plane.

**Set of values.** Location and orientation of turtle.

**API.**

```
public class Turtle

    Turtle(double x0, double y0, double a0)      create a new turtle at (x0, y0) facing a0
                                                    degrees counterclockwise from the x-axis

    void turnLeft(double delta)                  rotate delta degrees counterclockwise

    void goForward(double step)                 move distance step, drawing a line

    // Draw a square.
    Turtle turtle = new Turtle(0.0, 0.0, 0.0);
    turtle.goForward(1.0);           turtle.turnLeft
    (90.0);                      turtle.goForward(1.0);
    turtle.turnLeft(90.0);         turtle.goForward(1.0);
    turtle.turnLeft(90.0);         turtle.goForward(1.0);
    turtle.turnLeft(90.0);
```


## Turtle Graphics Implementation

```
public class Turtle
{
    private double x, y; // turtle is at (x, y)
    private double angle; // facing this direction

    public Turtle(double x0, double y0, double a0)
    {
        x = x0;
        y = y0;
        angle = a0;
    }

    public void turnLeft(double delta)
    {
        angle += delta;
    }


    public void goForward(double d)
    {
        double oldx = x;
        double oldy = y;
        x += d * Math.cos(Math.toRadians(angle));
        y += d * Math.sin(Math.toRadians(angle));
        StdDraw.line(oldx, oldy, x, y);
    }
}
```



17

### Turtle client example: N-gon


```
public class Ngon
{
    public static void main(String[] args)
    {
        int N      = Integer.parseInt(args[0]);
        double angle = 360.0 / N;
        double step = Math.sin(Math.toRadians(angle/2.0));
        Turtle turtle = new Turtle(0.5, 0, angle/2.0);
        for (int i = 0; i < N; i++)
        {
            turtle.goForward(step);
            turtle.turnLeft(angle);
        }
    }
}
```



3




7




1440

### Turtle client example: Spira Mirabilis


```
public class Spiral
{
    public static void main(String[] args)
    {
        int N      = Integer.parseInt(args[0]);
        double decay = Double.parseDouble(args[1]);
        double angle = 360.0 / N;
        double step = Math.sin(Math.toRadians(angle/2.0));
        Turtle turtle = new Turtle(0.5, 0, angle/2.0);
        for (int i = 0; i < 10 * N; i++)
        {
            step /= decay;
            turtle.goForward(step);
            turtle.turnLeft(angle);
        }
    }
}
```




3 1.0



3 1.2



1440 1.00004



1440 1.0004

19


18

## Spira Mirabilis in Nature



21

## Complex Numbers



©Copyright 2007 G.J.Caulkins www.mightywombat.com

### Complex Number Data Type

**Goal.** Create a data type to manipulate complex numbers.

**Set of values.** Two real numbers: real and imaginary parts.

#### API.

```
public class Complex  
  
    Complex(double real, double imag)  
  
    Complex plus(Complex b)          sum of this number and b  
    Complex times(Complex b)        product of this number and b  
    double abs()                  magnitude  
    String toString()             string representation
```

$$\begin{aligned} a &= 3 + 4i, \quad b = -2 + 3i \\ a + b &= 1 + 7i \\ a \times b &= -18 + i \\ |a| &= 5 \end{aligned}$$

### Applications of Complex Numbers

**Relevance.** A quintessential mathematical abstraction.

#### Applications.

- **Fractals.**
- Impedance in RLC circuits.
- Signal processing and Fourier analysis.
- Control theory and Laplace transforms.
- Quantum mechanics and Hilbert spaces.
- ...

## Complex Number Data Type: A Simple Client

Client program. Uses data type operations to calculate something.

```
public static void main(String[] args)
{
    Complex a = new Complex( 3.0, 4.0);
    Complex b = new Complex(-2.0, 3.0);
    Complex c = a.times(b);
    StdOut.println("a = " + a);
    StdOut.println("b = " + b);
    StdOut.println("c = " + c);
}
```

result of c.toString()

```
% java TestClient
a = 3.0 + 4.0i
b = -2.0 + 3.0i
c = -18.0 + 1.0i
```


**Remark.** Can't write  $a = b*c$  since no operator overloading in Java.

25

## Mandelbrot Set

**Mandelbrot set.** A set of complex numbers.

**Plot.** Plot  $(x, y)$  black if  $z = x + y i$  is in the set, and white otherwise.



- No simple formula describes which complex numbers are in set.
- Instead, describe using an **algorithm**.

27

## Complex Number Data Type: Implementation

```
public class Complex
{
    private final double re;           instance variables
    private final double im;

    public Complex(double real, double imag) constructor
    {
        re = real;
        im = imag;
    }

    public String toString() methods
    {
        return re + " + " + im + "i";
    }

    public double abs()
    {
        return Math.sqrt(re*re + im*im);
    }

    public Complex plus(Complex b)
    {
        double real = re + b.re;
        double imag = im + b.im;
        return new Complex(real, imag);
    }

    public Complex times(Complex b)
    {
        double real = re * b.re - im * b.im;
        double imag = re * b.im + im * b.re;
        return new Complex(real, imag);
    }
}
```


refers to b's instance variable

26

## Mandelbrot Set

**Mandelbrot set.** Is complex number  $z_0$  is in set?

- Iterate  $z_{t+1} = (z_t)^2 + z_0$ .
- If  $|z_t|$  diverges to infinity, then  $z_0$  not in set; otherwise  $z_0$  is in set.



t	$z_t$
0	-1/2 + 0i
1	-1/4 + 0i
2	-7/16 + 0i
3	-79/256 + 0i
4	-26527/65536 + 0i
5	-1443801919/4294967296 + 0i

$z = -1/2$  is in Mandelbrot set

t	$z_t$
0	1 + i
1	1 + 3i
2	-7 + 7i
3	1 - 97i
4	-9407 - 193i
5	88454401 + 3631103i


$z = 1 + i$  not in Mandelbrot set

28

## Plotting the Mandelbrot Set


### Practical issues.

- Cannot plot infinitely many points.
- Cannot iterate infinitely many times.



### Approximate solution.

- Sample from an  $N$ -by- $N$  grid of points in the plane.
- Fact: if  $|z_t| > 2$  for any  $t$ , then  $z$  not in Mandelbrot set.
- Pseudo-fact: if  $|z_{255}| \leq 2$  then  $z$  "likely" in Mandelbrot set.



29

## Complex Number Data Type: Another Client

### Mandelbrot function with complex numbers.

- Is  $z$  in the Mandelbrot set?
- Returns white (definitely no) or black (probably yes).

```
public static Color mand(Complex z0)
{
    Complex z = z0;
    for (int t = 0; t < 255; t++)
    {
        if (z.abs() > 2.0) return Color.WHITE;
        z = z.times(z);
        z = z.plus(z0);
    }
    return Color.BLACK;
}
```

More dramatic picture: replace `Color.WHITE` with grayscale or color.

`new Color(255-t, 255-t, 255-t)`

30

## Complex Number Data Type: Another Client

Plot the Mandelbrot set in gray scale.


```
public static void main(String[] args)
{
    double xc    = Double.parseDouble(args[0]);
    double yc    = Double.parseDouble(args[1]);
    double size = Double.parseDouble(args[2]);
    int N = 512;
    Picture pic = new Picture(N, N);

    for (int i = 0; i < N; i++)
        for (int j = 0; j < N; j++)
    {
        double x0 = xc - size/2 + size*i/N;
        double y0 = yc - size/2 + size*j/N; ← scale to screen
        Complex z0 = new Complex(x0, y0); ← coordinates
        Color color = mand(z0);
        pic.set(i, N-1-j, color);
    }
    pic.show(); ← (0, 0) is upper left
}
```


31

## Mandelbrot Set

% java Mandelbrot - .5 0 2




% java Mandelbrot .1045 -.637 .01




32

## Mandelbrot Set


```
* java ColorMandelbrot -1.5 0 2 < mandel.txt
```





-1.5 0 .02




-1.5 0 .002



33



34



## Applications of Data Types

**Data type.** Set of values and collection of operations on those values.

**Simulating the physical world.**

- Java objects model real-world objects.
- Not always easy to make model reflect reality.
- Ex: charged particle, molecule, COS 126 student, ....

**Extending the Java language.**

- Java doesn't have a data type for every possible application.
- Data types enable us to add our own abstractions.
- Ex: complex, vector, polynomial, matrix, ....

36