



<http://algs4.cs.princeton.edu>

## 2.1 ELEMENTARY SORTS

---

- ▶ *rules of the game*
- ▶ *selection sort*
- ▶ *insertion sort*
- ▶ *shuffling*
- ▶ *comparators*



<http://algs4.cs.princeton.edu>

## 2.1 ELEMENTARY SORTS

---

- ▶ *rules of the game*
- ▶ *selection sort*
- ▶ *insertion sort*
- ▶ *shuffling*
- ▶ *comparators*

# Sorting problem

---

**Ex.** Student records in a university.

	Chen	3	A	(991) 878-4944	308 Blair
	Rohde	2	A	(232) 343-5555	343 Forbes
	Gazsi	4	B	(800) 867-5309	101 Brown
<b>item</b> →	<b>Furia</b>	<b>1</b>	<b>A</b>	<b>(766) 093-9873</b>	<b>101 Brown</b>
	Kanaga	3	B	(898) 122-9643	22 Brown
	Andrews	3	A	(664) 480-0023	097 Little
<b>key</b> →	<b>Battle</b>	4	C	(874) 088-1212	121 Whitman

**Sort.** Rearrange array of  $N$  items in ascending order by key.

Andrews	3	A	(664) 480-0023	097 Little
Battle	4	C	(874) 088-1212	121 Whitman
Chen	3	A	(991) 878-4944	308 Blair
Furia	1	A	(766) 093-9873	101 Brown
Gazsi	4	B	(800) 867-5309	101 Brown
Kanaga	3	B	(898) 122-9643	22 Brown
Rohde	2	A	(232) 343-5555	343 Forbes

# Sample sort client 1

---

**Goal.** Sort **any** type of data.

**Ex 1.** Sort random real numbers in ascending order.

 seems artificial (stay tuned for an application)

```
public class Experiment
{
    public static void main(String[] args)
    {
        int N = Integer.parseInt(args[0]);
        Double[] a = new Double[N];
        for (int i = 0; i < N; i++)
            a[i] = StdRandom.uniform();
        Insertion.sort(a);
        for (int i = 0; i < N; i++)
            StdOut.println(a[i]);
    }
}
```

```
% java Experiment 10
0.08614716385210452
0.09054270895414829
0.10708746304898642
0.21166190071646818
0.363292849257276
0.460954145685913
0.5340026311350087
0.7216129793703496
0.9003500354411443
0.9293994908845686
```

# Sample sort client 2

---

**Goal.** Sort **any** type of data.

**Ex 2.** Sort strings in alphabetical order.

```
public class StringSorter
{
    public static void main(String[] args)
    {
        String[] a = StdIn.readAllStrings();
        Insertion.sort(a);
        for (int i = 0; i < a.length; i++)
            StdOut.println(a[i]);
    }
}
```

```
% more words3.txt
bed bug dad yet zoo ... all bad yes
```

```
% java StringSorter < words3.txt
all bad bed bug dad ... yes yet zoo
[suppressing newlines]
```

# Total order

---

**Goal.** Sort **any** type of data (for which sorting is well defined).

A **total order** is a binary relation  $\leq$  that satisfies:

- Antisymmetry: if both  $v \leq w$  and  $w \leq v$ , then  $v = w$ .
- Transitivity: if both  $v \leq w$  and  $w \leq x$ , then  $v \leq x$ .
- Totality: either  $v \leq w$  or  $w \leq v$  or both.

**Ex.**


- Standard order for natural and real numbers.
- Chronological order for dates or times.
- Lexicographic order for strings.

**Not transitive.** Ro-sham-bo.

**Not total.** PU course prerequisites.



**violates transitivity**



**violates totality**

# Callbacks

---

**Goal.** Sort **any** type of data (for which sorting is well defined).

**Q.** How can `sort()` compare data of type `Double`, `String`, and `java.io.File` without hardwiring in type-specific information.

**Callback = reference to executable code.**

- Client passes array of objects to `sort()` function.
- The `sort()` function calls object's `compareTo()` method as needed.

**Implementing callbacks.**

- Java: interfaces.
- C: function pointers.
- C++: class-type functors.
- C#: delegates.
- Python, Perl, ML, Javascript: first-class functions.

# Callbacks: Java interfaces

---

**Interface.** Specifies a set of methods that a concrete class can provide.

```
public interface Comparable<Item>
{
    public int compareTo(Item that);
}
```

contract: one method  
with this signature  
and prescribed behavior

**Concrete class.** Can provide the set of methods in the interface.

```
public class String implements Comparable<String>
{
    ...
    public int compareTo(String that)
    {
        ...
    }
}
```

class promises to  
honor the contract

class honors  
the contract

**Impact.**

- You can treat any `String` object as an object of type `Comparable`.
- On a `Comparable` object, you can invoke the `compareTo()` method.
- Enables **callbacks**.

"polymorphism"



# Callbacks: roadmap

## client (StringSorter.java)

```
public class StringSorter
{
    public static void main(String[] args)
    {
        String[] a = StdIn.readAllStrings();
        Insertion.sort(a);
        for (int i = 0; i < a.length; i++)
            StdOut.println(a[i]);
    }
}
```

## java.lang.Comparable interface

```
public interface Comparable<Item>
{
    public int compareTo(Item that);
}
```

## sort implementation (Insertion.java)

```
public static void sort(Comparable[] a)
{
    int N = a.length;
    for (int i = 0; i < N; i++)
        for (int j = i; j > 0; j--)
            if (a[j].compareTo(a[j-1]) < 0)
                exch(a, j, j-1);
            else break;
}
```

## data type implementation (String.java)

```
public class String
implements Comparable<String>
{
    ...
    public int compareTo(String that)
    {
        ...
    }
}
```

key point: no dependence  
on type of data to be sorted

## Elementary sorts: quiz 1

---

Suppose that the Java architects leave out `implements Comparable<String>` in the class declaration for `String`. What would be the effect?




- A. `String.java` won't compile.
- B. `StringSorter.java` won't compile.
- C. `Insertion.java` won't compile.
- D. `Insertion.java` will throw a run-time exception.
- E. *I don't know.*

# java.lang.Comparable API

---

Implement `compareTo()` so that `v.compareTo(w)`

- Defines a total order.
- Returns a negative integer, zero, or positive integer if  $v$  is less than, equal to, or greater than  $w$ , respectively.
- Throws an exception if incompatible types (or either is `null`).



**Built-in comparable types.** Integer, Double, String, Date, File, ...

**User-defined comparable types.** Implement the Comparable interface.

# Implementing the Comparable interface

---

**Date data type.** Simplified version of `java.util.Date`.

```
public class Date implements Comparable<Date>
{
    private final int month, day, year;

    public Date(int m, int d, int y)
    {
        month = m;
        day    = d;
        year   = y;
    }

    public int compareTo(Date that)
    {
        if (this.year < that.year ) return -1;
        if (this.year > that.year ) return +1;
        if (this.month < that.month) return -1;
        if (this.month > that.month) return +1;
        if (this.day < that.day  ) return -1;
        if (this.day > that.day  ) return +1;
        return 0;
    }
}
```



can compare Date objects  
only to other Date objects



<http://algs4.cs.princeton.edu>

## 2.1 ELEMENTARY SORTS


---

- ▶ *rules of the game*
- ▶ *selection sort*
- ▶ *insertion sort*
- ▶ *shuffling*
- ▶ *comparators*

# Selection sort demo

---

- In iteration  $i$ , find index  $\min$  of smallest remaining entry.
- Swap  $a[i]$  and  $a[\min]$ .



initial




# Selection sort

---

**Algorithm.** ↑ scans from left to right.

**Invariants.**

- Entries the left of ↑ (including ↑) fixed and in ascending order.
- No entry to right of ↑ is smaller than any entry to the left of ↑.



# Selection sort inner loop

To maintain algorithm invariants:

- Move the pointer to the right.

```
i++;
```

- Identify index of minimum entry on right.

```
int min = i;  
for (int j = i+1; j < N; j++)  
    if (less(a[j], a[min]))  
        min = j;
```

- Exchange into position.

```
exch(a, i, min);
```





## Two useful sorting abstractions

---

**Helper functions.** Refer to data only through compares and exchanges.

**Less.** Is item  $v$  less than  $w$ ?

```
private static boolean less(Comparable v, Comparable w)
{   return v.compareTo(w) < 0;   }
```

**Exchange.** Swap item in array  $a[]$  at index  $i$  with the one at index  $j$ .

```
private static void exch(Object[] a, int i, int j)
{
    Object swap = a[i];
    a[i] = a[j];
    a[j] = swap;
}
```

# Selection sort: Java implementation

---

```
public class Selection
{
    public static void sort(Comparable[] a)
    {
        int N = a.length;
        for (int i = 0; i < N; i++)
        {
            int min = i;
            for (int j = i+1; j < N; j++)
                if (less(a[j], a[min]))
                    min = j;
            exch(a, i, min);
        }
    }

    private static boolean less(Comparable v, Comparable w)
    { /* see previous slide */ }

    private static void exch(Object[] a, int i, int j)
    { /* see previous slide */ }
}
```

# Generic methods

---

Oops. The compiler complains.

```
% javac Selection.java
Note: Selection.java uses unchecked or unsafe operations.
Note: Recompile with -Xlint:unchecked for details.
```

```
% javac -Xlint:unchecked Selection.java
Selection.java:83: warning: [unchecked] unchecked call to
compareTo(T) as a member of the raw type java.lang.Comparable
    return (v.compareTo(w) < 0);
                   ^
1 warning
```

Q. How to silence the compiler?

# Generic methods

---

Pedantic (type-safe) version. Compiles without any warnings.

generic type variable  
(type inferred from argument; must be Comparable)

```
public class SelectionPedantic
{
    public static <Key extends Comparable<Key>> void sort(Key[] a)
    { /* as before */ }

    private static <Key extends Comparable<Key>> boolean less(Key v, Key w)
    { /* as before */ }

    private static Object void exch(Object[] a, int i, int j)
    { /* as before */ }
}
```

<http://algs4.cs.princeton.edu/21elementary/SelectionPedantic.java.html>

**Remark.** Use type-safe version in system code (but not in lecture).

# Selection sort: animations

---

20 random items




- ▲ algorithm position
- █ in final order
- ▒ not in final order

<http://www.sorting-algorithms.com/selection-sort>

# Selection sort: animations

---

20 partially-sorted items



- ▲ algorithm position
- █ in final order
- ▒ not in final order

<http://www.sorting-algorithms.com/selection-sort>

# Elementary sorts: quiz 1

---

How many compares does selection sort make to sort an array of  $N$  keys?

- A.  $\sim N$
- B.  $\sim 1/4 N^2$
- C.  $\sim 1/2 N^2$
- D.  $\sim N^2$
- E. *I don't know.*

# Selection sort: mathematical analysis

**Proposition.** Selection sort uses  $(N-1) + (N-2) + \dots + 1 + 0 \sim N^2/2$  compares and  $N$  exchanges to sort any array of  $N$  items.

		a[]										
i	min	0	1	2	3	4	5	6	7	8	9	10
		S	O	R	T	E	X	A	M	P	L	E
0	6	S	O	R	T	E	X	A	M	P	L	E
1	4	A	O	R	T	E	X	S	M	P	L	E
2	10	A	E	R	T	O	X	S	M	P	L	E
3	9	A	E	E	T	O	X	S	M	P	L	R
4	7	A	E	E	L	O	X	S	M	P	T	R
5	7	A	E	E	L	M	X	S	O	P	T	R
6	8	A	E	E	L	M	O	S	X	P	T	R
7	10	A	E	E	L	M	O	P	X	S	T	R
8	8	A	E	E	L	M	O	P	R	S	T	X
9	9	A	E	E	L	M	O	P	R	S	T	X
10	10	A	E	E	L	M	O	P	R	S	T	X
		A	E	E	L	M	O	P	R	S	T	X

*entries in black are examined to find the minimum*

*entries in red are a[min]*

*entries in gray are in final position*

Trace of selection sort (array contents just after each exchange)

**Running time insensitive to input.** Quadratic time, even if input is sorted.

**Data movement is minimal.** Linear number of exchanges—exactly  $N$ .





<http://algs4.cs.princeton.edu>

## 2.1 ELEMENTARY SORTS

---

- ▶ *rules of the game*
- ▶ *selection sort*
- ▶ *insertion sort*
- ▶ *shuffling*
- ▶ *comparators*

# Insertion sort demo

---

- In iteration  $i$ , swap  $a[i]$  with each larger entry to its left.



<https://www.youtube.com/watch?v=ROaIU379I3U>


# Insertion sort

---

**Algorithm.** ↑ scans from left to right.

**Invariants.**

- Entries to the left of ↑ (including ↑) are in ascending order.
- Entries to the right of ↑ have not yet been seen.



# Insertion sort: inner loop

To maintain algorithm invariants:

- Move the pointer to the right.

```
i++;
```



- Moving from right to left, exchange  $a[i]$  with each larger entry to its left.

```
for (int j = i; j > 0; j--)  
    if (less(a[j], a[j-1]))  
        exch(a, j, j-1);  
    else break;
```



# Insertion sort: Java implementation

---

```
public class Insertion
{
    public static void sort(Comparable[] a)
    {
        int N = a.length;
        for (int i = 0; i < N; i++)
            for (int j = i; j > 0; j--)
                if (less(a[j], a[j-1]))
                    exch(a, j, j-1);
                else break;
    }

    private static boolean less(Comparable v, Comparable w)
    { /* as before */ }


    private static void exch(Object[] a, int i, int j)
    { /* as before */ }
}
```

<http://algs4.cs.princeton.edu/21elementary/Insertion.java.html>

# Insertion sort: animation

---

40 random items



▲ algorithm position  
█ in order  
▒ not yet seen

<http://www.sorting-algorithms.com/insertion-sort>

# Insertion sort: mathematical analysis

**Proposition.** To sort a randomly-ordered array with distinct keys, insertion sort uses  $\sim \frac{1}{4} N^2$  compares and  $\sim \frac{1}{4} N^2$  exchanges on average.

**Pf.** Expect each entry to move halfway back.

		a[]										
i	j	0	1	2	3	4	5	6	7	8	9	10
		S	O	R	T	E	X	A	M	P	L	E
1	0	O	S	R	T	E	X	A	M	P	L	E
2	1	O	R	S	T	E	X	A	M	P	L	E
3	3	O	R	S	T	E	X	A	M	P	L	E
4	0	E	O	R	S	T	X	A	M	P	L	E
5	5	E	O	R	S	T	X	A	M	P	L	E
6	0	A	E	O	R	S	T	X	M	P	L	E
7	2	A	E	M	O	R	S	T	X	P	L	E
8	4	A	E	M	O	P	R	S	T	X	L	E
9	2	A	E	L	M	O	P	R	S	T	X	E
10	2	A	E	E	L	M	O	P	R	S	T	X
		A	E	E	L	M	O	P	R	S	T	X

*entries in gray do not move*

*entry in red is a[j]*

*entries in black moved one position right for insertion*

Trace of insertion sort (array contents just after each insertion)

## Elementary sorts: quiz 2

---

How many compares does insertion sort make to sort an array of  $N$  distinct keys in reverse order?


- A.  $\sim N$
- B.  $\sim 1/4 N^2$
- C.  $\sim 1/2 N^2$
- D.  $\sim N^2$
- E. *I don't know.*



# Insertion sort: animation

---

40 reverse-sorted items



<http://www.sorting-algorithms.com/insertion-sort>

## Insertion sort: analysis

---

**Worst case.** If the array is in descending order (and no duplicates), insertion sort makes  $\sim \frac{1}{2} N^2$  compares and  $\sim \frac{1}{2} N^2$  exchanges.

X T S R P O M L F E A


**Best case.** If the array is in ascending order, insertion sort makes  $N-1$  compares and 0 exchanges.

A E E L M O P R S T X

# Insertion sort: animation

---

40 partially-sorted items



- ▲ algorithm position
- █ in order
- █ not yet seen

<http://www.sorting-algorithms.com/insertion-sort>

# Insertion sort: partially-sorted arrays

---

**Def.** An **inversion** is a pair of keys that are out of order.

A E E L M O T R X P S

T-R T-P T-S R-P X-P X-S

(6 inversions)

**Def.** An array is **partially sorted** if the number of inversions is  $\leq cN$ .

- Ex 1. A sorted array has 0 inversions.
- Ex 2. A subarray of size 10 appended to a sorted subarray of size  $N$ .

**Proposition.** For partially-sorted arrays, insertion sort runs in linear time.

**Pf.** Number of exchanges equals the number of inversions.

↑  
number of compares  $\leq$  exchanges +  $(N - 1)$

# Insertion sort: practical improvements

---

**Half exchanges.** Shift items over (instead of exchanging).

- Eliminates unnecessary data movement.
- No longer uses only `less()` and `exch()` to access data.


A C H H I M N N P Q X Y K B I N A R Y

tmp =

**Binary insertion sort.** Use binary search to find insertion point.

- Number of compares  $\sim N \lg N$ .
- But still a quadratic number of array accesses to move items.

A C H H I **M** N N P Q X Y K B I N A R Y



binary search for first key > K

## Elementary sorts: quiz 3

---

Which is faster in practice, selection sort or insertion sort?

- A. Selection sort.
- B. Insertion sort.
- C. No significant difference.
- D. *I don't know.*



<http://algs4.cs.princeton.edu>

## 2.1 ELEMENTARY SORTS

---


- ▶ *rules of the game*
- ▶ *selection sort*
- ▶ *insertion sort*
- ▶ *shuffling*
- ▶ *comparators*

# Interview question: shuffle an array

---

**Goal.** Rearrange array so that result is a uniformly random permutation.

all  $N!$  permutations  
equally likely






# Interview question: shuffle an array

---

**Goal.** Rearrange array so that result is a uniformly random permutation.


all  $N!$  permutations  
equally likely



# Shuffle sort

---


- Generate a random real number for each array entry.
- Sort the array.



# Shuffle sort

---


- Generate a random real number for each array entry.
- Sort the array.



# Shuffle sort

---

- Generate a random real number for each array entry.
- Sort the array.



**Proposition.** Shuffle sort produces a uniformly random permutation.

**Application.** Shuffle columns in a spreadsheet.

← assuming real numbers are uniformly random (and no ties)

# War story (Microsoft)

---

Microsoft antitrust probe by EU. Microsoft agreed to provide a randomized ballot screen for users to select browser in Windows 7.

<http://www.browserchoice.eu>

## Select your web browser(s)



A fast new browser from Google. Try it now!



Safari for Windows from Apple, the world's most innovative browser.



Your online security is Firefox's top priority. Firefox is free, and made to help you get the most out of the



The fastest browser on Earth. Secure, powerful and easy to use, with excellent privacy protection.



Designed to help you take control of your privacy and browse with confidence. Free from Microsoft.



appeared last 50% of the time

# War story (Microsoft)

---

Microsoft antitrust probe by EU. Microsoft agreed to provide a randomized ballot screen for users to select browser in Windows 7.

**Solution?** Implement shuffle sort by making comparator always return a random answer.


```
public int compareTo(Browser that)
{
    double r = Math.random();
    if (r < 0.5) return -1;
    if (r > 0.5) return +1;
    return 0;
}
```

← browser comparator  
(should implement a total order)

# Knuth shuffle

---

- In iteration  $i$ , pick integer  $r$  between 0 and  $i$  uniformly at random.
- Swap  $a[i]$  and  $a[r]$ .



**Proposition.** [Fisher-Yates 1938] Knuth shuffling algorithm produces a uniformly random permutation of the input array in linear time.

↖ assuming integers  
uniformly at random

# Knuth shuffle

---

- In iteration  $i$ , pick integer  $r$  between 0 and  $i$  uniformly at random.
- Swap  $a[i]$  and  $a[r]$ .

common bug: between 0 and  $N - 1$   
correct variant: between  $i$  and  $N - 1$

```
public class Knuth
{
    public static void shuffle(Object[] a)
    {
        int N = a.length;
        for (int i = 0; i < N; i++)
        {
            int r = StdRandom.uniform(i + 1);
            exch(a, i, r);
        }
    }
}
```

← between 0 and  $i$

<http://algs4.cs.princeton.edu/11model/Knuth.java.html>




# Broken Knuth shuffle

---

Q. What happens if integer is chosen between 0 and  $N-1$  ?

A. Not uniformly random!

instead of  
between 0 and  $i$



permutation	Knuth shuffle	broken shuffle
A B C	$1 / 6$	$4 / 27$
A C B	$1 / 6$	$5 / 27$
B A C	$1 / 6$	$5 / 27$
B C A	$1 / 6$	$5 / 27$
C A B	$1 / 6$	$4 / 27$
C B A	$1 / 6$	$4 / 27$

probability of each permutation when shuffling { A, B, C }

# War story (online poker)

Texas hold'em poker. Software must shuffle electronic cards.



How We Learned to Cheat at Online Poker: A Study in Software Security

[http://www.cigital.com/papers/download/developer\\_gambling.php](http://www.cigital.com/papers/download/developer_gambling.php)

# War story (online poker)

---

Shuffling algorithm in FAQ at [www.planetpoker.com](http://www.planetpoker.com)

```
for i := 1 to 52 do begin
  r := random(51) + 1; ← between 1 and 51
  swap := card[r];
  card[r] := card[i];
  card[i] := swap;
end;
```

- Bug 1.** Random number  $r$  never 52  $\Rightarrow$  52<sup>nd</sup> card can't end up in 52<sup>nd</sup> place.
- Bug 2.** Shuffle not uniform (should be between 1 and  $i$ ).
- Bug 3.** `random()` uses 32-bit seed  $\Rightarrow$   $2^{32}$  possible shuffles.
- Bug 4.** Seed = milliseconds since midnight  $\Rightarrow$  86.4 million shuffles.

*“ The generation of random numbers is too important to be left to chance. ”*

*— Robert R. Coveyou*

# War story (online poker)

---

## Best practices for shuffling (if your business depends on it).

- Use a hardware random-number generator that has passed both the FIPS 140-2 and the NIST statistical test suites.
- Continuously monitor statistic properties:  
hardware random-number generators are fragile and fail silently.
- Use an unbiased shuffling algorithm.



RANDOM.ORG

**Bottom line.** Shuffling a deck of cards is hard!



<http://algs4.cs.princeton.edu>


## 2.1 ELEMENTARY SORTS

---

- ▶ *rules of the game*
- ▶ *selection sort*
- ▶ *insertion sort*
- ▶ *shuffling*
- ▶ ***comparators***



# Sort music library by artist



The screenshot shows a music player interface. At the top, several album covers are displayed in a perspective view. The central cover is for Bruce Springsteen's "Born In The U.S.A.". Below the covers, a table lists songs sorted by artist. The table has columns for Name, Artist, Time, and Album. The song "Dancing In The Dark" by Bruce Springsteen is highlighted in blue.

	Name	Artist	Time	Album
12	<input checked="" type="checkbox"/> Let It Be	The Beatles	4:03	Let It Be
13	<input checked="" type="checkbox"/> Take My Breath Away	BERLIN	4:13	Top Gun - Soundtrack
14	<input checked="" type="checkbox"/> Circle Of Friends	Better Than Ezra	3:27	Empire Records
15	<input checked="" type="checkbox"/> Dancing With Myself	Billy Idol	4:43	Don't Stop
16	<input checked="" type="checkbox"/> Rebel Yell	Billy Idol	4:49	Rebel Yell
17	<input checked="" type="checkbox"/> Piano Man	Billy Joel	5:36	Greatest Hits Vol. 1
18	<input checked="" type="checkbox"/> Pressure	Billy Joel	3:16	Greatest Hits, Vol. II (1978 - 1985) (Disc 2)
19	<input checked="" type="checkbox"/> The Longest Time	Billy Joel	3:36	Greatest Hits, Vol. II (1978 - 1985) (Disc 2)
20	<input checked="" type="checkbox"/> Atomic	Blondie	3:50	Atomic: The Very Best Of Blondie
21	<input checked="" type="checkbox"/> Sunday Girl	Blondie	3:15	Atomic: The Very Best Of Blondie
22	<input checked="" type="checkbox"/> Call Me	Blondie	3:33	Atomic: The Very Best Of Blondie
23	<input checked="" type="checkbox"/> Dreaming	Blondie	3:06	Atomic: The Very Best Of Blondie
24	<input checked="" type="checkbox"/> Hurricane	Bob Dylan	8:32	Desire
25	<input checked="" type="checkbox"/> The Times They Are A-Changin'	Bob Dylan	3:17	Greatest Hits
26	<input checked="" type="checkbox"/> Livin' On A Prayer	Bon Jovi	4:11	Cross Road
27	<input checked="" type="checkbox"/> Beds Of Roses	Bon Jovi	6:35	Cross Road
28	<input checked="" type="checkbox"/> Runaway	Bon Jovi	3:53	Cross Road
29	<input checked="" type="checkbox"/> Rasputin (Extended Mix)	Boney M	5:50	Greatest Hits
30	<input checked="" type="checkbox"/> Have You Ever Seen The Rain	Bonnie Tyler	4:10	Faster Than The Speed Of Night
31	<input checked="" type="checkbox"/> Total Eclipse Of The Heart	Bonnie Tyler	7:02	Faster Than The Speed Of Night
32	<input checked="" type="checkbox"/> Straight From The Heart	Bonnie Tyler	3:41	Faster Than The Speed Of Night
33	<input checked="" type="checkbox"/> Holding Out For A Hero	Bonny Tyler	5:49	Meat Loaf And Friends
34	<input checked="" type="checkbox"/> Dancing In The Dark	Bruce Springsteen	4:05	Born In The U.S.A.
35	<input checked="" type="checkbox"/> Thunder Road	Bruce Springsteen	4:51	Born To Run
36	<input checked="" type="checkbox"/> Born To Run	Bruce Springsteen	4:30	Born To Run
37	<input checked="" type="checkbox"/> Jungleland	Bruce Springsteen	9:34	Born To Run
38	<input checked="" type="checkbox"/> Turtl Turtl Turtl (To Everything)	The Birds	3:57	Forest Gump The Soundtrack (Disc 2)

# Sort music library by song name



The screenshot shows a music player interface. At the top, there is a carousel of album covers. The central cover is for Bon Jovi's 'Cross Road'. Below the carousel is a progress bar. Underneath the progress bar is a table listing songs in a music library, sorted by name. The song 'Beds Of Roses' by Bon Jovi is highlighted in blue, indicating it is the current selection.

	Name	Artist	Time	Album
1	<input checked="" type="checkbox"/> Alive	Pearl Jam	5:41	Ten
2	<input checked="" type="checkbox"/> All Over The World	Pixies	5:27	Bossanova
3	<input checked="" type="checkbox"/> All Through The Night	Cyndi Lauper	4:30	She's So Unusual
4	<input checked="" type="checkbox"/> Allison Road	Gin Blossoms	3:19	New Miserable Experience
5	<input checked="" type="checkbox"/> Ama, Ama, Ama Y Ensancha El ...	Extremoduro	2:34	Deltoya (1992)
6	<input checked="" type="checkbox"/> And We Danced	Hooters	3:50	Nervous Night
7	<input checked="" type="checkbox"/> As I Lay Me Down	Sophie B. Hawkins	4:09	Whaler
8	<input checked="" type="checkbox"/> Atomic	Blondie	3:50	Atomic: The Very Best Of Blondie
9	<input checked="" type="checkbox"/> Automatic Lover	Jay-Jay Johanson	4:19	Antenna
10	<input checked="" type="checkbox"/> Baba O'Riley	The Who	5:01	Who's Better, Who's Best
11	<input checked="" type="checkbox"/> Beautiful Life	Ace Of Base	3:40	The Bridge
12	<input checked="" type="checkbox"/> Beds Of Roses	Bon Jovi	6:35	Cross Road
13	<input checked="" type="checkbox"/> Black	Pearl Jam	5:44	Ten
14	<input checked="" type="checkbox"/> Bleed American	Jimmy Eat World	3:04	Bleed American
15	<input checked="" type="checkbox"/> Borderline	Madonna	4:00	The Immaculate Collection
16	<input checked="" type="checkbox"/> Born To Run	Bruce Springsteen	4:30	Born To Run
17	<input checked="" type="checkbox"/> Both Sides Of The Story	Phil Collins	6:43	Both Sides
18	<input checked="" type="checkbox"/> Bouncing Around The Room	Phish	4:09	A Live One (Disc 1)
19	<input checked="" type="checkbox"/> Boys Don't Cry	The Cure	2:35	Staring At The Sea: The Singles 1979-1985
20	<input checked="" type="checkbox"/> Brat	Green Day	1:43	Insomniac
21	<input checked="" type="checkbox"/> Breakdown	Deerheart	3:40	Deerheart
22	<input checked="" type="checkbox"/> Bring Me To Life (Kevin Roen Mix)	Evanescence Vs. Pa...	9:48	
23	<input checked="" type="checkbox"/> Californication	Red Hot Chili Pepp...	1:40	
24	<input checked="" type="checkbox"/> Call Me	Blondie	3:33	Atomic: The Very Best Of Blondie
25	<input checked="" type="checkbox"/> Can't Get You Out Of My Head	Kylie Minogue	3:50	Fever
26	<input checked="" type="checkbox"/> Celebration	Kool & The Gang	3:45	Time Life Music Sounds Of The Seventies - C
27	<input checked="" type="checkbox"/> Chaina Chaina	Sukhwinder Singh	5:11	Bombay Dreams



# Comparable interface: review

---

**Comparable interface:** sort using a type's **natural order**.

```
public class Date implements Comparable<Date>
{
    private final int month, day, year;

    public Date(int m, int d, int y)
    {
        month = m;
        day    = d;
        year   = y;
    }
    ...
    public int compareTo(Date that)
    {
        if (this.year < that.year ) return -1;
        if (this.year > that.year ) return +1;
        if (this.month < that.month) return -1;
        if (this.month > that.month) return +1;
        if (this.day    < that.day  ) return -1;
        if (this.day    > that.day  ) return +1;
        return 0;
    }
}
```

natural order





# Comparator interface

---

Comparator interface: sort using an **alternate order**.

```
public interface Comparator<Item>
{
    public int compare(Item v, Item w);
}
```

Required property. Must be a **total order**.

string order	example
<b>natural order</b>	Now is the time
<b>case insensitive</b>	is Now the time
<b>Spanish language</b>	café cafetero cuarto <b>churro</b> nube <b>ñoño</b>
<b>British phone book</b>	McKinley Mackintosh

# Comparator interface: system sort

---

## To use with Java system sort:

- Create Comparator object.
- Pass as second argument to `Arrays.sort()`.

```
String[] a;  
...  
Arrays.sort(a);  
...  
Arrays.sort(a, String.CASE_INSENSITIVE_ORDER);  
...  
Arrays.sort(a, Collator.getInstance(new Locale("es")));  
...  
Arrays.sort(a, new BritishPhoneBookOrder());  
...
```

uses natural order

uses alternate order defined by  
Comparator<String> object

**Bottom line.** Decouples the definition of the data type from the definition of what it means to compare two objects of that type.

# Comparator interface: using with our sorting libraries

---

To support comparators in our sort implementations:

- Pass Comparator to both sort() and less(), and use it in less().
- Use Object instead of Comparable.

```
import java.util.Comparator;

public class Insertion
{
    ...

    public static void sort(Object[] a, Comparator comparator)
    {
        int N = a.length;
        for (int i = 0; i < N; i++)
            for (int j = i; j > 0 && less(comparator, a[j], a[j-1]); j--)
                exch(a, j, j-1);
    }

    private static boolean less(Comparator comparator, Object v, Object w)
    { return comparator.compare(v, w) < 0; }
}
```

<http://algs4.cs.princeton.edu/21elementary/Insertion.java.html>

<http://algs4.cs.princeton.edu/21elementary/InsertionPedantic.java.html>

# Comparator interface: implementing

---

## To implement a comparator:

- Define a (nested) class that implements the Comparator interface.
- Implement the compare() method.
- Provide client access to Comparator.

```
import java.util.Comparator;

public class Student
{
    private final String name;
    private final int section;
    ...

    public static Comparator<Student> byNameOrder()
    { return new NameOrder(); }

    private static class NameOrder implements Comparator<Student>
    {
        public int compare(Student v, Student w)
        { return v.name.compareTo(w.name); }
    }

    ...
}
```

one Comparator for the class

# Comparator interface: implementing

---

## To implement a comparator:


- Define a (nested) class that implements the Comparator interface.
- Implement the compare() method.
- Provide client access to Comparator.

```
import java.util.Comparator;

public class Student
{
    private final String name;
    private final int section;
    ...

    public static Comparator<Student> bySectionOrder()
    { return new SectionOrder(); }

    private static class SectionOrder implements Comparator<Student>
    {
        public int compare(Student v, Student w)
        { return v.section - w.section; }
    }
    ...
}
```

 this trick works here  
since no danger of overflow

# Comparator interface: implementing

---

## To implement a comparator:

- Define a (nested) class that implements the Comparator interface.
- Implement the `compare()` method.
- Provide client access to Comparator.

`Insertion.sort(a, Student.byNameOrder());`

Andrews	3	A	(664) 480-0023	097 Little
Battle	4	C	(874) 088-1212	121 Whitman
Chen	3	A	(991) 878-4944	308 Blair
Fox	3	A	(884) 232-5341	11 Dickinson
Furia	1	A	(766) 093-9873	101 Brown
Gazsi	4	B	(800) 867-5309	101 Brown
Kanaga	3	B	(898) 122-9643	22 Brown
Rohde	2	A	(232) 343-5555	343 Forbes

`Insertion.sort(a, Student.bySectionOrder());`

Furia	1	A	(766) 093-9873	101 Brown
Rohde	2	A	(232) 343-5555	343 Forbes
Andrews	3	A	(664) 480-0023	097 Little
Chen	3	A	(991) 878-4944	308 Blair
Fox	3	A	(884) 232-5341	11 Dickinson
Kanaga	3	B	(898) 122-9643	22 Brown
Battle	4	C	(874) 088-1212	121 Whitman
Gazsi	4	B	(800) 867-5309	101 Brown

# Stability

---

A typical application. First, sort by name; **then** sort by section.

`Selection.sort(a, Student.byNameOrder());`

Andrews	3	A	(664) 480-0023	097 Little
Battle	4	C	(874) 088-1212	121 Whitman
Chen	3	A	(991) 878-4944	308 Blair
Fox	3	A	(884) 232-5341	11 Dickinson
Furia	1	A	(766) 093-9873	101 Brown
Gazsi	4	B	(800) 867-5309	101 Brown
Kanaga	3	B	(898) 122-9643	22 Brown
Rohde	2	A	(232) 343-5555	343 Forbes

`Selection.sort(a, Student.bySectionOrder());`

Furia	1	A	(766) 093-9873	101 Brown
Rohde	2	A	(232) 343-5555	343 Forbes
Chen	3	A	(991) 878-4944	308 Blair
Fox	3	A	(884) 232-5341	11 Dickinson
Andrews	3	A	(664) 480-0023	097 Little
Kanaga	3	B	(898) 122-9643	22 Brown
Gazsi	4	B	(800) 867-5309	101 Brown
Battle	4	C	(874) 088-1212	121 Whitman

@#%&@! Students in section 3 no longer sorted by name.

A **stable** sort preserves the relative order of items with equal keys.

## Elementary sorts: quiz 4

---

Which sorting algorithms are stable?

- A. Selection sort.
- B. Insertion sort.
- C. Both A and B.
- D. Neither A nor B.
- E. *I don't know.*



# Stability: insertion sort

**Proposition.** Insertion sort is **stable**.

```
public class Insertion
{
    public static void sort(Comparable[] a)
    {
        int N = a.length;
        for (int i = 0; i < N; i++)
            for (int j = i; j > 0 && less(a[j], a[j-1]); j--)
                exch(a, j, j-1);
    }
}
```

i	j	0	1	2	3	4
0	0	B <sub>1</sub>	A <sub>1</sub>	A <sub>2</sub>	A <sub>3</sub>	B <sub>2</sub>
1	0	A <sub>1</sub>	B <sub>1</sub>	A <sub>2</sub>	A <sub>3</sub>	B <sub>2</sub>
2	1	A <sub>1</sub>	A <sub>2</sub>	B <sub>1</sub>	A <sub>3</sub>	B <sub>2</sub>
3	2	A <sub>1</sub>	A <sub>2</sub>	A <sub>3</sub>	B <sub>1</sub>	B <sub>2</sub>
4	4	A <sub>1</sub>	A <sub>2</sub>	A <sub>3</sub>	B <sub>1</sub>	B <sub>2</sub>
		A <sub>1</sub>	A <sub>2</sub>	A <sub>3</sub>	B <sub>1</sub>	B <sub>2</sub>

**Pf.** Equal items never move past each other.

# Stability: selection sort

---

**Proposition.** Selection sort is **not stable**.

```
public class Selection
{
    public static void sort(Comparable[] a)
    {
        int N = a.length;
        for (int i = 0; i < N; i++)
        {
            int min = i;
            for (int j = i+1; j < N; j++)
                if (less(a[j], a[min]))
                    min = j;
            exch(a, i, min);
        }
    }
}
```

i	min	0	1	2
0	2	B <sub>1</sub>	B <sub>2</sub>	A
1	1	A	B <sub>2</sub>	B <sub>1</sub>
2	2	A	B <sub>2</sub>	B <sub>1</sub>
		A	B <sub>2</sub>	B <sub>1</sub>

**Pf by counterexample.** Long-distance exchange can move one equal item past another one.