

Assignment Operator



Issue: What about assignment?

Thought process

- Must have a way to assign a value to a variable
- Many high-level languages provide an assignment **statement**
- Would be more expressive to define an assignment **operator**
 - Performs assignment, and then *evaluates to the assigned value*
 - Allows assignment to appear within larger expressions

Decisions

- Provide assignment operator: =
- Define assignment operator so it changes the value of a variable, and also evaluates to that value

7

Assignment Operator Examples



Examples

```
i = 0;
/* Side effect: assign 0 to i.
   Evaluate to 0.

j = i = 0; /* Assignment op has R to L associativity */
/* Side effect: assign 0 to i.
   Evaluate to 0.
   Side effect: assign 0 to j.
   Evaluate to 0. */

while ((i = getchar()) != EOF) ...
/* Read a character.
   Side effect: assign that character to i.
   Evaluate to that character.
   Compare that character to EOF.
   Evaluate to 0 (FALSE) or 1 (TRUE). */
```

8

Special-Purpose Assignment



Issue: Should C provide tailored assignment operators?

Thought process

- The construct `a = b + c` is flexible
- The construct `i = i + c` is somewhat common
- The construct `i = i + 1` is very common
- Special-purpose operators make code more expressive
 - Might reduce some errors
 - May complicate the language and compiler

Decisions

- Introduce += operator to do things like `i += c`
- Extend to -= *= /= ~= &= |= ^= <<= >=
- Special-case increment and decrement: `i++ i--`
- Provide both pre- and post-inc/dec: `x = ++i; y = i++;`

9

iClicker Question

Q: What are `i` and `j` set to in the following code?

```
i = 5;
j = i++;
j += ++i;
```

- A. 5, 7
- B. 7, 5
- C. 7, 11
- D. 7, 12
- E. 7, 13

sizeof Operator



Issue: How to determine the sizes of data?

Thought process

- The sizes of most primitive types are un- or under-specified
- Provide a way to find size of a given variable programmatically

Decisions

- Provide a `sizeof` operator
 - Applied at compile-time
 - Operand can be a **data type**
 - Operand can be an **expression**, from which the compiler infers a data type

Examples, on courselab using gcc217

- `sizeof(int)` evaluates to 4
- `sizeof(i)` evaluates to 4 (where `i` is a variable of type `int`)

11

iClicker Question

Q: What is the value of the following `sizeof` expression on the courselab machines?

```
int i = 1;
sizeof(i + 2L)
```

- A. 3
- B. 4
- C. 8
- D. 12
- E. error

Other Operators



Issue: What other operators should C have?

Decisions

- Function call operator
 - Should mimic the familiar mathematical notation
 - `function(param1, param2, ...)`
- Conditional operator: `?:`
 - The only ternary operator: "inline if statement"
 - Example: `(i < j) ? i : j` evaluates to min of `i` and `j`
 - See King book for details
- Sequence operator: `,`
 - See King book
- Pointer-related operators: `& *`
 - Described later in the course
- Structure-related operators (`.` `->`)
 - Described later in the course

13

Operators Summary: C vs. Java



Java only

- `>>>` right shift with zero fill
- `new` create an object
- `instanceof` is left operand an object of class right operand?

C only

- `->` structure member select
- `*` dereference
- `&` address of
- `,` sequence
- `sizeof` compile-time size of

14

History of programming languages: goto, if-then-else, while-do



What the computer does:

```
/* add up the first n numbers */
```

1. `s = 0;`
2. `i = 1;`
3. `if (i>n) goto 7`
4. `s = s + i;`
5. `i = i + 1;`
6. `goto 3`
7. `/* answer in s */`

Early programming languages (1950s)

```
s=0;
i=1;
LOOP: if i>n goto DONE
s=s+1;
i=i+1;
goto LOOP;
DONE:
```

Control Statements




- **Algol-60 language (1960)**
 - **if-then-else, while-do, for loop, goto**
- Scientific background
 - **Boehm and Jacopini** proved (1966) that any algorithm can be expressed as the nesting of only 3 control structures:




Barry Boehm


Sequence



Selection



Repetition



16

Control Statements (cont.)



- Thought Process (cont.)
 - **Dijkstra** argued that any algorithm **should** be expressed using only those control structures (*GOTO Statement Considered Harmful* paper, 1968)
- C language design (1972)
 - Basically follow ALGOL-60, but use `{ braces }` instead of the more heavyweight `BEGIN – END` syntax.




Edsger Dijkstra

17


Sequence Statement



Sequence



Compound statement, alias block




18

Selection Statements



Selection



```
if (expr)
    statement1;
```

```
if (expr)
    statement1;
else
    statement2;
```

19

Selection Statements



switch and **break** statements, for multi-path decisions on a single *integerExpr*

```
switch (integerExpr)
{
    case integerLiteral1:
        ...
        break;
    case integerLiteral2:
        ...
        break;
    ...
    default:
        ...
}
```


What happens if you forget **break**?

20

Repetition Statements




while statement; test at leading edge




```
while (expr)
    statement;
```

for statement; test at leading edge, increment at trailing edge



```
for (initExpr; testExpr; incrExpr)
    bodyStatement;
```

do...while statement; test at trailing edge



```
do
    statement;
while (expr);
```

21

Other Control Statements



Issue: What other control statements should C provide?

Decisions

- **break** statement (revisited)
 - Breaks out of closest enclosing **switch** or repetition statement
- **continue** statement
 - Skips remainder of current loop iteration
 - Continues with next loop iteration
 - When used within **for**, still executes *incrementExpr*
- **goto** statement grudgingly provided
 - Jump to specified **label**

22

Declaring Variables



Issue: Should C require variable declarations?

Thought process:

- Declaring variables allows compiler to check spelling
- Declaring variables allows compiler to allocate memory more efficiently

23

Declaring Variables



Decisions:

- Require variable declarations
- Provide **declaration statement**
- Programmer specifies type of variable (and other attributes too)

Examples

- `int i;`
- `int i, j;`
- `int i = 5;`
- `const int i = 5; /* value of i cannot change */`
- `static int i; /* covered later in course */`
- `extern int i; /* covered later in course */`

24

Declaring Variables



Decisions (cont.):

- Unlike Java, declaration statements **must** appear before any other kind of statement in compound statement

```
{
  int i;
  /* Non-declaration
  stmts that use i. */
  ...
  int j;
  /* Non-declaration
  stmts that use j. */
  ...
}
```

Illegal in C

```
{
  int i;
  int j;
  ...
  /* Non-declaration
  stmts that use i. */
  ...
  /* Non-declaration
  stmts that use j. */
  ...
}
```

Legal in C

25

Repetition Statements



Decisions (cont.)

- Similarly, cannot declare loop control variable in `for` statement

```
{
  ...
  for (int i = 0; i < 10; i++)
    /* Do something */
  ...
}
```

Illegal in C

```
{
  int i;
  ...
  for (i = 0; i < 10; i++)
    /* Do something */
  ...
}
```

Legal in C

26

Statements Summary: C vs. Java



Java only

- Declarations anywhere within block
- Declare immutable variables with `final`
- Conditionals of type `boolean`
- “Labeled” `break` and `continue`
- No `goto`

C only

- Declarations only at beginning block
- Declare immutable variables with `const`
- Conditionals of any type (checked for zero / nonzero)
- No “labeled” `break` and `continue`
- `goto` provided (but don't use it)

27

iClicker Question

Q: What does the following code print?

```
int i = 1;
switch (i++) {
  case 1: printf("%d", ++i);
  ...
  case 2: printf("%d", i++);
}
```

- A. 1
- B. 2
- C. 3
- D. 22
- E. 33

I/O Facilities



Issue: Should C provide I/O facilities?

Thought process

- Unix provides the **file** abstraction
 - A file is a sequence of characters with an indication of the current position
- Unix provides 3 standard files
 - Standard input, standard output, standard error
- C should be able to use those files, and others
- I/O facilities are complex
- C should be small/simple

29

I/O Facilities



Decisions

- Do not provide I/O facilities in the **language**
- Instead provide I/O facilities in **standard library**
 - **Constant:** `EOF`
 - **Data type:** `FILE` (described later in course)
 - **Variables:** `stdin`, `stdout`, and `stderr`
 - **Functions:** ...

30

Reading Characters



Issue: What functions should C provide for reading characters from standard input?

Thought process

- Need function to read a single character from `stdin`
- Function must have a way to indicate failure, that is, to indicate that no characters remain

Decisions

- Provide `getchar()` function
- Make return type of `getchar()` wider than `char`
 - Make it `int`; that's the natural word size
- Define `getchar()` to return `EOF` (a special non-character `int`) to indicate failure

Note

- There is no such thing as "the `EOF` character"

31

Writing Characters



Issue: What functions should C provide for writing a character to standard output?

Thought process

- Need function to write a single character to `stdout`

Decisions

- Provide a `putchar()` function
- Define `putchar()` to accept one parameter
 - For symmetry with `getchar()`, parameter should be an `int`

32

Reading Other Data Types



Issue: What functions should C provide for reading data of other primitive types?

Thought process

- Must convert external form (sequence of character codes) to internal form
- Could provide `getshort()`, `getint()`, `getfloat()`, etc.
- Could provide one parameterized function to read any primitive type of data

Decisions

- Provide `scanf()` function
- Can read any primitive type of data
- First parameter is a **format string** containing **conversion specifications**

See King book for details

33

Writing Other Data Types



Issue: What functions should C provide for writing data of other primitive types?

Thought process

- Must convert internal form to external form (sequence of character codes)
- Could provide `putshort()`, `putint()`, `putfloat()`, etc.
- Could provide one parameterized function to write any primitive type of data

Decisions

- Provide `printf()` function
- Can write any primitive type of data
- First parameter is a **format string** containing **conversion specifications**

See King book for details

34

Other I/O Facilities



Issue: What other I/O functions should C provide?

Decisions

- `fopen()`: Open a stream
- `fclose()`: Close a stream
- `fgetc()`: Read a character from specified stream
- `fputc()`: Write a character to specified stream
- `fgets()`: Read a line/string from specified stream
- `fputs()`: Write a line/string to specified stream
- `fscanf()`: Read data from specified stream
- `fprintf()`: Write data to specified stream

Described in King book, and later in the course after covering files, arrays, and strings

35

Summary



C design decisions and the goals that affected them

- Data types (last time)
- Operators
- Statements
- I/O facilities

Knowing the design goals and how they affected the design decisions can yield a rich understanding of C

36

