
COS 217: Introduction to Programming Systems

Storage Hierarchy, Caching, and Locality



Typical Storage Hierarchy



Typical Storage Hierarchy

Factors to consider:

- Capacity
- Latency (how long to do a read)
- Bandwidth (how many bytes/sec can be read)
 - Weakly correlated to latency: reading 1 MB from a hard disk isn't much slower than reading 1 byte
- Volatility
 - Do data persist in the absence of power?

4

• Capacity: 32KB to 32MB

Typical Storage Hierarchy

Main memory (RAM)

• Latency: 0 cycles


L1/L2/L3 Cache

Registers

• **Latency**: ~ 50-100 cycles

• Latency: 1 to 40 cycles


- 100 times slower than registers
- Capacity: GB







Ochristianw, Ocharrisonbroadbent



Typical Storage Hierarchy

Local secondary storage: disk drives

- Solid-State Disk (SSD):
 - Flash memory (nonvolatile)
 - Latency: 0.1 ms (~ 300k cycles)
 - Capacity: 128 GB 2 TB
- Hard Disk:

- Spinning magnetic platters, moving heads
- Latency: 10 ms (~ 30M cycles)
- Capacity: 1 10 TB









Cache / RAM Latency








Typical Storage Hierarchy

Remote secondary storage

- (a.k.a. "the cloud")
 - Latency: tens of milliseconds
 - Limited by network bandwidth
 - Capacity: essentially unlimited





Storage Device Speed vs. Size

Facts:

- CPU needs sub-nanosecond access to data to run instructions at full speed
- Fast storage (sub-nanosecond) is small (100-1000 bytes)
- Big storage (gigabytes) is slow (15 nanoseconds)
- Huge storage (terabytes) is glacially slow (milliseconds)

Goal:

- Need many gigabytes of memory,
- but with fast (sub-nanosecond) average access time

Solution: locality allows caching

- Most programs exhibit good locality
- A program that exhibits good locality will benefit from proper caching, which enables good average performance

Locality



Two kinds of **locality**

- Temporal locality
 - If a program references item X now, it probably will reference X again soon
- Spatial locality
 - If a program references item X now, it probably will reference item at address X±1 soon

Most programs exhibit good temporal and spatial locality

Locality example

sum = 0; for (i = 0; i < n; i++) sum += a[i];

- Temporal locality
 - *Data:* Whenever the CPU accesses Sum, it accesses Sum again shortly thereafter
 - Instructions: Whenever the CPU executes sum += a[i], it executes sum += a[i] again shortly thereafter

Typical code

(good locality)

Spatial locality

- Data: Whenever the CPU accesses a [i], it accesses a [i+1] shortly thereafter
- Instructions: Whenever the CPU executes sum += a[i], it executes i++ shortly thereafter



Caching



Cache


- Fast access, small capacity storage device
- Acts as a staging area for a subset of the items in a slow access, large capacity storage device

Good locality + proper caching

- \Rightarrow Most storage accesses can be satisfied by cache
- \Rightarrow Overall storage performance improved

Caching in a Storage Hierarchy





Cache Hits and Misses

Cache hit

- E.g., request for block 10
- Access block 10 at level k
- Fast!


Cache miss

- E.g., request for block 8
- Evict some block from level k
- Load block 8 from level k+1 to level k
- Access block 8 at level k
- Slow!

14

Caching goal:

- Maximize cache hits
- Minimize cache misses





Cache Eviction Policies

Best eviction policy: "oracle"

- Always evict a block that is *never* accessed again, or...
- Always evict the block accessed the furthest in the future
- Impossible in the general case

Worst eviction policy

- Always evict the block that will be accessed next!
- Causes thrashing
- Impossible in the general case!

Cache Eviction Policies

Reasonable eviction policy: LRU policy

- Evict the "Least Recently Used" (LRU) block
 - With the assumption that it will not be used again (soon)
- Good for straight-line code
- (can be) bad for (large) loops
- Expensive to implement
 - Often simpler approximations are used
 - See Wikipedia "Page replacement algorithm" topic





Here's a real question from an old exam:

For caching in a memory hierarchy,

what is the best motivation for a *larger* cache block size?

- A. Temporal Locality
- B. Spatial Locality
- C. Both
- D. Neither

В

Spatial locality makes use of subsequent data after a given read, so having more data to keep reading is a win.



Locality/Caching Example: Matrix Multiplication

Matrix multiplication

- Matrix = two-dimensional array
- Multiply n-by-n matrices A and B
- Store product in matrix C


Performance depends upon

- Effective use of caching (as implemented by **system**)
- Good locality (as implemented by you)

Locality/Caching Example: Matrix Mult




Two-dimensional arrays are stored in either **row-major** or **column-major** order



row-majoi		r col-major		
a[0][0]	18	a[0][0]	18	
a[0][1]	19	a[1][0]	21	
a[0][2]	20	a[2][0]	24	
a[1][0]	21	a[0][1]	19	
a[1][1]	22	a[1][1]	22	
a[1][2]	23	a[2][1]	25	
a[2][0]	24	a[0][2]	20	
a[2][1]	25	a[1][2]	23	
a[2][2]	26	a[2][2]	26	


C uses row-major order


- Access in row-major order \Rightarrow good spatial locality
- Access in column-major order \Rightarrow poor spatial locality



Reasonable cache effects


- Good locality for A
- Bad locality for B
- Good locality for C






Poor cache effects


- Bad locality for A
- Bad locality for B
- Bad locality for C





Good cache effects

- Good locality for A
- Good locality for B
- Good locality for C





Another ghost of exams past ...



Suppose that C laid out arrays in memory in column-major order instead of row-major order. What would be the most efficient loop ordering for this matrix multiplication to maximize performance through good locality?

- A. i k j (Same as row-major)
- B. ijk
- C. jki
- D. jik
- E. kij

F. kji

23

C:jki

Exactly what makes this bad for all three in row-major makes it ideal for columnmajor: a and c have good spatial b has good temporal, spatial

Storage Hierarchy & Caching Issues

Issue: Block size?

Large block size:

- + do data transfer less often
- + take advantage of spatial locality
- longer time to complete data transfer
- less advantage of temporal locality

Small block size: the opposite

Typical: Lower in pyramid \Rightarrow slower data transfer \Rightarrow larger block sizes

Device	Block Size
Register	8 bytes
L1/L2/L3 cache line	128 bytes
Main memory page	4KB or 64KB
Disk block	512 bytes to 4KB
Disk transfer block	4KB (4096 bytes) to 64MB (67108864 bytes)



Storage Hierarchy & Caching Issues



Issue: Who manages the cache?

Device	Managed by:
Registers (cache of L1/L2/L3 cache and main memory)	Compiler, using complex code- analysis techniques Assembly lang programmer
L1/L2/L3 cache (cache of main memory)	Hardware, using simple algorithms
Main memory (cache of local sec storage)	Hardware and OS, using virtual memory with complex algorithms (since accessing disk is expensive)
Local secondary storage (cache of remote sec storage)	End user, by deciding which files to download

Next time ...



