Procedure Call

CS 217

Procedure Call

- Involves following actions
  - pass arguments
  - save a return address
  - transfer control to callee
  - transfer control back to caller
  - return results
- Simplest example: leaf procedure (`a=b*c;`)

```
ld   b,%o0        ld   b,%o0
ld   c,%o1        call .mul
call .mul         ld   c,%o1
nop               st   %o0,a
st   %o0,a
```


Call/Return Instructions

- Procedures are called with either…

`call` *label*



leaves PC (location of `call`) in `%o7` (`%r15`)

`jmpl` *address,reg*



leaves PC in *reg*

Call/Return (cont)

- Indirect calls

  `jmpl` *reg*`,%r15`

  jumps to the 32-bit address specified in *reg*

  leaves PC (return address) in `%r15`

  e.g., for function pointers `a = (*apply)(b,c);`

```
ld   b,%o0
ld   c,%o1
ld   apply,%o3
jmpl %o3,%r15; nop
st   %o0,a
```


Call/Return (cont)

- Procedure call return

  `jmpl %r15+8,%g0`

  transfers control from caller to callee

  other instructions: `ret` and `retl`

  why `+8`?

Nested/Recursive Calls

- **`A`** calls **`B`**, which calls **`C`**



  must work when **`B`** is **`A`**

Nested/Recursive Calls (cont)

- Other requirements
  - pass a variable number of arguments
  - pass and return structures
  - allocate and deallocate space for local variables
  - save and restore caller's registers
- Entry and exit sequences collaborate to implement these requirements

Stack

- Procedure call information stored on stack
  - locals, including compiler temporaries
  - caller's registers, if necessary
  - callee's arguments, if necessary
- Sparc's stack grows "down" from high to low address
- The stack pointer (`%sp`) points to top word on the stack (must be multiple of 8)

Arguments and Return Values

- By convention
  - caller places arguments in the "out" registers
  - callee finds its arguments in the "in" registers
  - only the first 6 arguments are passed in registers
  - the rest are passed on the stack
- Registers at call time

caller	callee	
`%o7`	`%i7`	return address -8
`%o6`	`%i6`	stack/frame pointer
`%o5`	`%i5`	sixth argument
…	…	
`%o0`	`%i0`	first argument

Arguments/Return Value (cont)

- Registers at return time

callee	caller	
`%i5`	`%o5`	sixth return value
`%i4`	`%o4`	fifth return value
…	…	
`%i0`	`%o0`	first return value

Register Windows

- Each procedure gets 16 "new" registers
- The window "slides" at call time
  - caller's out registers become synonymous with callee's in registers
- Instructions
  - **`save`** slides the window forward
  - **`restore`** slides the window backwards
  - decrement/increments CWP register
- Finite number of windows (usually 8)

Register Windows (cont)



Window Managment

- Call time (**`save`**)
  - **`save %sp,`***N*`,%sp`** e.g., **`save %sp,-4*16,%sp`**
  - current window becomes previous window
  - decrements CWP and checks for overflow
  - adds *N* to the stack pointer (allocates *N* bytes if *N*<0)
  - if overflow occurs, save registers on the stack (must be enough stack space)
- Return time (**`restore`**)
  - previous window becomes current window
  - increments CWP and checks for underflow

Window Management (cont)

- In both **`save`** and **`restore`**
  - source registers refer to current window
  - destination registers refer to new window

Stack Frame



Example Stack Frames

```
main() {
   t(1,2,3,4,5,6,7,8);
}
t(int a1, int a2, int a3, int a4,
  int a5, int a6, int a7, int a8) {
    int b1 = a1;
    return s(b1,a8);
}
s(int c1, int c2) {
   return c1 + c2;
}
```


Example (cont)

```
_main: save %sp,-104,%sp
       set 1,%o0
       set 2,%o1
       set 3,%o2
       set 4,%o3
       set 5,%o4
       set 6,%05
       set 7,%i5
       st %i5,[%sp+4*6+68]
       set 8,%i5
       st %i5,[%sp+4*7+68]
       call _t; nop
       ret; restore
```


Example (cont)

```
_t: save %sp,-96,%sp
    st %i0,[%fp-4]
    ld [%fp-4],%o0
    ld [%fp+96],%o1
    call _s; nop
    mov %o0,%i0
    ret; restore

_s: add %o0,%01,%o0
    retl; nop
```


main
t
a8
a7
a6
a5
a4
a3
a2
a1
struct *
16 words
b1
c2
c1
struct *
16 words
+96
+92
+88
+64
%fp
-4
+88
+84
+64
%sp