



## The C Programming Language

### Part 1



1

## For Your Amusement



“C is quirky, flawed, and an enormous success. While accidents of history surely helped, it evidently satisfied a need for a system implementation language efficient enough to displace assembly language, yet sufficiently abstract and fluent to describe algorithms and interactions in a wide variety of environments.”

– Dennis Ritchie

2

## Goals of this Lecture



### Help you learn about:

- The decisions that were made by the designers\* of C
- **Why** they made those decisions  
... and thereby...
- The fundamentals of C

### Why?

- Learning the design rationale of the C language provides a richer understanding of C itself
- A power programmer knows both the programming language and its design rationale

\* Dennis Ritchie, then later, members of standardization committees

3

## Historical context - 1972



Operating systems were programmed in assembly language (i.e., in machine instructions)

[Efficient; expressive; easy to translate to machine language; but not portable from one computer instruction set to another; hard to write programs, hard to debug, maintain...]

Application programs were in “high-level” languages such as Algol, COBOL, PL/1, (newly invented) Pascal

Goals of these languages: Ease of programming, expressiveness, structured programming, safety, data structures, portability

Not fully achieved: safety, expressiveness, portability

Not even attempted: modularity

## Goals for C language - 1972



Program operating-systems in a “high-level” language

Need: ease of programming, (reasonable) expressiveness, structured programming, data structures, **modularity**, compatible on a 64-kilobyte computer

**Don't even attempt: safety**

**When possible, have a bit of: portability**

## Goals for C language - 1972



Program operating-systems in a “high-level” language

Need: ease of programming, (reasonable) expressiveness, structured programming, data structures, **modularity**, compatibility

**Don't even attempt: safety**

**When possible, have a bit of: portability**

## Goals for Java language - 1995

(reasonable) ease of programming, (reasonable) expressiveness, structured programming, data structures,

**modularity, safety, portability, automatic memory management**

It's not that Java was particularly innovative (in these respects).

By 1995, decades of computer-science research had made it straightforward to achieve all these goals at once.

In 1972, nobody knew how.

## Goals of C

Designers wanted C to:	But also:
Support system programming	Support application programming
Be low-level	Be portable
Run fast	Be portable
Be easy for people to handle	Be easy for computers to handle

Conflicting goals on multiple dimensions!

7

## Agenda

Data Types

Operators

Statements

I/O Facilities

8

## Primitive Data Types

- integer data types
- floating-point data types
- no character data type (use small integer types instead)
- no character string data type (use arrays of small ints instead)
- no logical or boolean data types (use integers instead)

9

## Integer Data Types

- integer data types: `char`, `short`, `int`, `long`
- `char` is 1 byte
  - Number of bits per byte is unspecified! (but in the 21<sup>st</sup> century, pretty safe to assume it's 8)
- sizes of other integer type is not fully specified but *constrained*:
  - `int` is natural word size
  - $2 \leq \text{sizeof}(\text{short}) \leq \text{sizeof}(\text{int}) \leq \text{sizeof}(\text{long})$

### On CourseLab

- Natural word size: 4 bytes (but not really!)
- `char`: 1 byte
- `short`: 2 bytes
- `int`: 4 bytes
- `long`: 8 bytes

What decisions did the designers of Java make?

10

## Integer Literals

- Decimal: 123
- Octal: 0173 = 123
- Hexadecimal: 0x7B = 123
- Use "L" suffix to indicate `long` literal
- No suffix to indicate `short` literal; instead must use cast

### Examples

- `int`: 123, 0173, 0x7B
- `long`: 123L, 0173L, 0x7BL
- `short`: (short)123, (short)0173, (short)0x7B

11

## Unsigned Integer Data Types

Both signed and unsigned integer data types

12

## Unsigned Integer Data Types

### Both signed and unsigned integer data types

- signed integer types: `int`, `short`, `long`
- unsigned integer types: `unsigned char`, `unsigned short`, `unsigned int`, and `unsigned long`
- `char` might mean `signed char` or `unsigned char`;
- Define conversion rules for mixed-type expressions
  - Generally, mixing signed and unsigned converts signed to unsigned
- See King book Section 7.4 for details

What decisions did the designers of Java make?

13

## Unsigned Integer Literals

### Decisions

- Default is signed
- Use "U" suffix to indicate unsigned literal

### Examples

- unsigned int:**
  - `123U`, `0173U`, `0x7BU`
  - `123`, `0173`, `0x7B` will work just fine in practice; technically there is an implicit cast from signed to unsigned, but in these cases it shouldn't make a difference.
- unsigned long:**
  - `123UL`, `0173UL`, `0x7BUL`
- unsigned short:**
  - `(unsigned short)123`, `(unsigned short)0173`, `(unsigned short)0x7B`

14

## Signed and Unsigned Integer Literals

### The rules:

The type is the first one that can represent the literal without overflow

Literal	Data Type
<code>dd...d</code>	<code>int</code> <code>long</code> <code>unsigned long</code>
<code>Odd...d</code> <code>0xdd...d</code>	<code>int</code> <code>unsigned int</code> <code>long</code> <code>unsigned long</code>
<code>dd...dU</code> <code>Odd...dU</code> <code>0xdd...dU</code>	<code>unsigned int</code> <code>unsigned long</code>
<code>dd...dL</code> <code>Odd...dL</code> <code>0xdd...dL</code>	<code>long</code> <code>unsigned long</code>
<code>dd...dUL</code> <code>Odd...dUL</code> <code>0xdd...dUL</code>	<code>unsigned long</code>

15

## Character Data Types

Back in 1972, some computers had 6-bit bytes, some had 7-bit bytes, some had 8-bit bytes; the C language had to accommodate all these

By 1985, pretty much all computers had 8-bit bytes

- The ASCII character code fits in 7 bits
- One character per byte
- It would be a very strange 21<sup>st</sup>-century C compiler that supported other than 8-bit bytes

### The C character type

- `char` can hold an ASCII character
- `char` might be signed or unsigned, but since  $0 \leq \text{ASCII} \leq 127$  it doesn't really matter
- if you're using these for *arithmetic*, you might care to specify `signed char` or `unsigned char`

16

## Character Literals

- single quote syntax: `'a'`
- Use backslash (the **escape character**) to express special characters

### Examples (with numeric equivalents in ASCII):

```
'a'    the a character (97, 01100001s, 61s)
'\o141' the a character, octal character form
'\x61' the a character, hexadecimal character form
'b'    the b character (98, 01100010s, 62s)
'A'    the A character (65, 01000001s, 41s)
'B'    the B character (66, 01000010s, 42s)
'\0'   the null character (0, 00000000s, 0s)
'0'    the zero character (48, 00110000s, 30s)
'1'    the one character (49, 00110001s, 31s)
'\n'   the newline character (10, 00001010s, As)
'\t'   the horizontal tab character (9, 00001001s, 9s)
'\'    the backslash character (92, 01011100s, 5Cs)
'\''   the single quote character (96, 01100000s, 60s)
```

17

## Strings and String Literals

**Issue: How should C represent strings and string literals?**

### Rationale:

- Natural to represent a string as a sequence of contiguous chars
- How to know where char sequence ends?
  - Store length before char sequence?
  - Store special "sentinel" char after char sequence?

18

## Strings and String Literals

**Decisions**

- Adopt a convention
  - String is a sequence of contiguous chars
  - String is terminated with null char ('\0')
- Use double-quote syntax (e.g. "hello") to represent a string literal
- Provide no other language features for handling strings
  - Delegate string handling to standard library functions

**Examples**

- 'a' is a char literal
- "abcd" is a string literal
- "a" is a string literal

How many bytes?


What decisions did the designers of Java make?

19

## Unicode and UTF-8

Back in 1970s, English was the only language in the world, so we only needed this alphabet:

In the 21<sup>st</sup> century, it turns out that there are other people and languages out there, so we need:



ASCII: American Standard Code for Information Interchange

20

## Unicode and UTF-8

But Unicode characters are 24 bits; how to encode them in 8-bit bytes?

Obvious solution: 3 bytes per char.

Problem 1: Then, '\n'=0x0a might not mean newline (if it's one of the bytes of a 3-byte sequence)

Problem 2: wastes a lot of space for English text

Solution: UTF-8 encoding of Unicode

<http://www.cprogramming.com/tutorial/unicode.html>  
(This won't be on the exam...)

21

## Logical Data Types

- no logical or Boolean data type
- Represent logical data using type char
  - Or any integer type
  - Or any primitive type!!!
- Convention: 0 ⇒ FALSE, ≠0 ⇒ TRUE
- Convention used by:
  - Relational operators (<, >, etc.)
  - Logical operators (!, &&, ||)
  - Statements (if, while, etc.)

22

## Aside: Logical Data Type Shortcuts

**Note**

- Using integer data to represent logical data permits shortcuts

```

int i;
...
if (i) /* same as (i != 0) */
    statement1;
else
    statement2;
...
    
```

23

## Aside: Logical Data Type Dangers

**Note**

- The lack of logical data type hampers compiler's ability to detect some errors with certainty

```

int i;
...
i = 0;
if (i = 5)
    statement1;
...
    
```

What happens in Java?

What happens in C?

24

## Floating-Point Data Types



Back in 1972, each brand of computer had a different (and slightly incompatible) representation of floating-point numbers

This was standardized in 1985; now practically all computers use the IEEE 754 Floating Point standard, designed by Prof. William Kahan of the Univ. of California at Berkeley

- three floating-point data types: `float`, `double`, and `long double`
- sizes unspecified, but constrained:  
`sizeof(float) ≤ sizeof(double) ≤ sizeof(long double)`

On CourseLab (and on pretty much any 21<sup>st</sup>-century computer)

- `float`: 4 bytes
- `double`: 8 bytes
- `long double`: 16 bytes

25

## Floating-Point Literals



- fixed-point or "scientific" notation
- Any literal that contains decimal point or "E" is floating-point
- The default floating-point type is `double`
- Append "F" to indicate `float`
- Append "L" to indicate `long double`

### Examples

- `double`: `123.456`, `1E-2`, `-1.23456E4`
- `float`: `123.456F`, `1E-2F`, `-1.23456E4F`
- `long double`: `123.456L`, `1E-2L`, `-1.23456E4L`

26

## Data Types Summary: C vs. Java



### Java only

- `boolean`, `byte`

### C only

- `unsigned char`, `unsigned short`, `unsigned int`, `unsigned long`

### Sizes

- **Java**: Sizes of all types are specified, and *portable*
- **C**: Sizes of all types except `char` are system-dependent

### Type char

- **Java**: `char` is 2 bytes (to hold all 1995-era Unicode values)
- **C**: `char` is 1 byte

27

Continued next lecture

28

## Agenda



Data Types

**Operators**

Statements

I/O Facilities

29