Basic Input/Output Functions

- C language has no I/O statements; use standard C ***library***
  - "**`#include <stdio.h>`**" before using the functions
  - **`int getchar(void)`** returns the next character in "stdin" or **`EOF`**
  - **`getchar()`** returns an **`int`**, not a **`char`**, to accommodate **`EOF`**
  - **`int putchar(int c)`** writes character **`c`** to the "stdout" and returns **`c`**
- A basic copy program:

```
#include <stdio.h>

int main(void) {
    int c;

    while ((c = getchar()) != EOF)
           putchar(c);
    return 0;
}
```

```
% copy < foo.c > bar.c
% copy < foo.c
% copy > bar.c
```


Formatted Output

- **`int printf(const char *format, ...)`**
- Writes **`format`** to stdout with the values of argument 2, 3, ..., ***n***

```
printf("error at line %d: %s\n", lineno, msg);
```

- ***Beware***:

  no type checking
  no type conversion
  no checking for the correct number of arguments

- Conversion specifications

`%d`	decimal	plus other formatting control, e.g. field widths
`%o`	octal	
`%x`	hexadecimal	
`%c`	char	
`%u`	unsigned	
`%e %f %g`	float & double	
`%s`	string	
`%%`	%	

- See **`sprintf`**, **`fprintf`**, **`vfprintf`**; and see **`scanf`**, **`fscanf`**, **`sscanf`** for ***input***
- See K&R, section 7.2 for more details

C Preprocessor

- C preprocessor manipulates ***text***

  file inclusion

  macros

  conditional compilation
- Invoked automatically by the C compiler

  try "**`lcc -E foo.c`**"
- File inclusion

  header files contain declarations for one or more C program files

  names of header file should end in "**`.h`**"

  specify system header filename with **`<...>`** — ***location independent***

```
#include <stdio.h>
#include "defs.h"
```


Macros

- Macros provide parameterized text substitution
- Macro ***definition***

```
#define MAXLINE 120
#define lower(c) ((c)-'A'+'a')
```

macro name — replacement (to the end of the line)

macro parameter name

- Macro ***replacement***

```
char buf[MAXLINE+1];    becomes    char buf[120+1];
c = lower(buf[i]);                 c = ((buf[i])-'A'+'a');
```

More on Macros

- use parentheses liberally:

```
#define plusone(x) x+1
i = 3*plusone(2);          becomes      what?

#define plusone(x) ((x)+1)
```

- avoid macros that use an argument more than ***once***

```
#define max(a,b) ((a)>(b)?(a):(b))
y = max(i++,j++);
    becomes      y = ((i++)>(j++)?(i++):(j++));
```

Copyright ©1995,1996. D. Hanson, K. Li, A. Rogers & J.P. Singh

Conditional Compilation

- Removing macro definitions

```
#undef plusone
```

- Conditional compilation

```
#ifdef name
#ifndef name
#if expr
#elif
#else
#endif
```

  - header file **`defs.h`**:

```
#ifndef DEFS_INCLUDED
#define DEFS_INCLUDED

#define MAXLINE 120
...
#endif
```

- Use conditional compilation ***sparingly***
- See K&R, section 4.11 for details

Copyright ©1995,1996. D. Hanson, K. Li, A. Rogers & J.P. Singh