Type Sizes

	year	72–81	80–92	64–92	93–?
	computer	DEC-10	PCs	IBM360 VAX 68020 SPARC MIPS	R4000 DEC Alpha
type	`char`	7	8	8	8
	`short`	18	16	16	16,32
	`int`	36	16,32	32	32,64
	`long`	36	32	32	**64**
	`float`	36	32	32	32
	`double`	72	64	64	64
	pointer	18	**16, 32**	32	**64**

Note: C did not exist in 1964; this table just reflects typical sizes

Copyright ©1995 D. Hanson, K. Li & J.P. Singh

Types

- The ***type*** of an object determines

  the ***values*** it can have and the ***operations*** that can be performed on it

- Basic types

`char`	a “character”; typically a “byte”
`int`	an integer; typically a “word”
`float`	single-precision floating point
`double`	double-precision floating point

- `int` qualifiers (optional)

  `short int` “smaller” `int`

  `long int` “bigger” `int`, but ***not*** double precision

- Unsigned integers: non-negative modulo where n is #bits/integer

  `unsigned int` `unsigned short int` `unsigned char`

- Is `char` signed or unsigned?

Copyright ©1995 D. Hanson, K. Li & J.P. Singh

Constant Expressions

- `Const` qualifier identifies ***read-only variables***

```
const double Pi = 3.14159;
const double TwoPi = 2*3.14159;
```

- ***Constant expressions*** are evaluated at ***compile time***

```
int p = 1 - 1;
int p = 1/0, x = 1 ? 0 : 1/0;
```

- Use constant expressions

  to reduce the number of `#define` constants

  to increase readability

  to improve changeability, e.g.

```
#define MAXLINE 120
...
char buf[2*MAXLINE + 1];
```

Copyright ©1995 D. Hanson, K. Li & J.P. Singh

Types of Constants

`char`	`'a'`	character constant (single quote)
	`'\035'`	character code `35` octal
	`'\x29'`	character code `29` hexadecimal
	`'\t'`	tab (`'\011'`, do “`man ascii`” for details)
	`'\n'`	newline (`'\012'`)
	`'\\'`	backslash
	`'\''`	single quote
	`'\b'`	backspace (`'\010'`)
	`'\0'`	null character
`int`	`156`	decimal constant
	`0234`	octal
	`0x9c`	hexadecimal
`long`	156L	
	156l	for sanity, use upper-case L
`float`	15.6f	
	1.56e1F	
`double`	15.6	“plain” floating point constants are `double`s
	15.6L	
	15.6l	

Copyright ©1995 D. Hanson, K. Li & J.P. Singh

Strings & Initialization

- "Strings" are arrays of characters

  "**hello\n**"

  the compiler always provides a terminating **'\0'**

- Array length can be ***derived*** from initialization

```
char hello[] = "hello\n";
```

  is equivalent to

```
char hello[7] = "hello\n";
char hello[7] = { 'h', 'e', 'l', 'l', 'o', '\n', '\0' }
```

- Ditto for arrays

```
int x[] = { 1, 2, 3 };
int y[][3] = {
    { 1, 3, 5 },
    { 2, 4, 6 },
    { 3, 5, 7 },
    { 4, 6, 8 }
};
```

  see K&R, sections 2.4 & 4.9 for more information

Copyright ©1995 D. Hanson, K. Li & J.P. Singh

Arrays

- Array declarations specify the ***number*** of elements, not the upper bound

```
int digits[10];
```

  digits is an array of 10 **int**s

```
digits[0], digits[1], ..., digits[9]
```

- Arrays may be indexed by any integer expression

```
digits[f(x)/2 + BASE]
```

- N***o bounds checking!***
- Multi-dimensional arrays

```
float matrix[3][4][5]
```

  a 3-dimensional array with elements

- Arrays are stored in ***row-major order***; last subscript varies "fastest"

```
matrix[0][0][0], matrix[0][0][1], ...
```

Copyright ©1995 D. Hanson, K. Li & J.P. Singh

Enumerations

- ***Enumerations*** associate constant values with identifiers

```
enum boolean { NO, YES };
```

```
enum color { RED, GREEN, BLUE };
```

- Values are generated and may be printed symbolically by debuggers
- Values can be given and unspecified ones automatically continue

```
enum escapes { BELL='\a', BACKSPACE='\b', TAB='\t'};
```

```
enum months { Jan=1, Feb, Mar, Apr, May, Jun, Jul,
    Aug, Sep, Oct, Nov, Dec };
```

- **enum** identifiers are **int** constants, but enumeration type may take less space

  sizeof NO is 4 bytes

  enum boolean flag; may occupy 1–4 bytes

- **enum** identifiers should have no ***conflicts***
- What is the difference between **enum** and #define?

Copyright ©1995 D. Hanson, K. Li & J.P. Singh