# Programming Style

CS 217

## Programming Style

- Who reads your code?
  - compiler
  - other programmers
- Which one cares about style?



```
typedef struct{double x,y,z}vec;vec U,black,amb={.02,.02,.02};struct sphere{
vec cen,color;double rad,kd,ks,kt,kl,ir}*s,*best,sph[]={0,6,.5,1,1,1,9,
.05,.2,.85,0,.1,7,-1,.8,-.5,1,.5,.2,1,,7,.3,0,,.05,1.2,1,.8,,-.5,1,.8,.8,
1,,.3,.7,0,.0,.1.2,3,,-6,.15,.1,,.8,1,,7,,0,.0,.0,.6,1.5,-3,,-3,.12,,.8,1,,
1,.5,.0,.0,.0,,.5,1.5,};yx;double u,b,tmin,sqrt(),tan();double vdot(A,B)vec A
,B;{return A.x*B.x+A.y*B.y+A.z*B.z;}vec vcomb(a,A,B)double a;vec A,B;{B.x+=a*
A.x;B.y+=a*A.y;B.z+=a*A.z;return B;}vec vunit(A)vec A;{return vcomb(1./sqrt(
vdot(A,A)),A,black);}struct sphere*intersect(P,D)vec P,D;{best=0;tmin=1e30;s=
sph+5;while(s--sph)b=vdot(D,U=vcomb(-1.,P,s->cen)),u=b*b-vdot(U,U)+s->rad*s ->
rad,u=u0?sqrt(u):1e31,u=b-u<1e-7?b+u:b+u,tmin=u>1e-7&&u<tmin?best=s,u:
tmin;return best;}vec trace(level,P,D)vec P,D;{double d,eta,e;vec N,color;
struct sphere*s,*l;if(!level--)return black;if(s=intersect(P,D)){s=best;
amb;color=amb;eta=s->ir;d= -vdot(D,N=vunit(vcomb(-1.,P=vcomb(tmin,D,P),s->cen
)));if(d<0)N=vcomb(-1.,N,black),eta=1/eta,d= -d;l=sph+5;while(l--sph)if((e=l ->
kl*vdot(N,U=vunit(vcomb(-1.,P,l->cen)))>0&&intersect(P,U)==l)color=vcomb(e ,l->
color,color);U=s->color;color.x*=U.x;color.y*=U.y;color.z*=U.z;e=1-eta* eta*(1-
d*d);return vcomb(s->kt,e>0?trace(level,P,vcomb(eta,D,vcomb(eta*d-sqrt
(e),N,black))):black,vcomb(s->ks,trace(level,P,vcomb(2*d,N,D)),vcomb(s->kd,
color,vcomb(s->kl,U,black))));}main(){printf("%d %d\n",32,32);while(yx<32*32)
U.x=yx%32-32/2,U.z=32/2-yx++/32,U.y=32/2/tan(25/114.591559026),U=vcomb(255.,
trace(3,black,vunit(U),black),printf("%.0f %.0f\n",U);}
```

This is a working ray tracer! (courtesy of Paul Heckbert)

## Programming Style

- Why does programming style matter?
  - Bugs are often created due to misunderstanding of programmer
    - What does this variable do?
    - How is this function called?
  - Good code == human readable code
- How can code become easier for humans to read?
  - Structure
  - Conventions
  - Documentation
  - Scope

```
int main()
{
  char *strings[MAX_STRINGS];
  int nstrings;

  ReadStrings(strings, &nstrings, MAX_STRINGS, stdin);
  SortStrings(strings, nstrings);
  WriteStrings(strings, nstrings, stdout);

  return 0;
}
```

## Structure

- Convey structure with layout and indentation
  - use white space freely
    e.g., to separate code into paragraphs
  - use indentation to emphasize structure
    use editor's autoindent facility
  - break long lines at logical places
    e.g., by operator precedence
  - line up parallel structures

```
alpha = angle(p1, p2, p3);
beta  = angle(p1, p2, p3);
gamma = angle(p1, p2, p3);
```

## Structure

- Convey structure with modules
  - separate modules in different files
    e.g., sort.c versus stringarray.c
  - simple, atomic operations in different functions
    e.g., ReadStrings, WriteStrings, SortStrings, etc.
  - separate distinct ideas within same function

```
#include "stringarray.h"

int main()
{
  char *strings[MAX_STRINGS];
  int nstrings;

  ReadStrings(strings, &nstrings, MAX_STRINGS, stdin);
  SortStrings(strings, nstrings);
  WriteStrings(strings, nstrings, stdout);

  return 0;
}
```

## Structure

- Convey structure with spacing and indenting
  - implement multiway branches with `if` ... `else if` ... `else`
  - emphasize that only one action is performed
  - avoid empty `then` and `else` actions
  - handle default action, even if can't happen (use `assert(0)`)
  - avoid `continue`; minimize use of `break` and `return`
  - avoid complicated nested structures

```
if (x < v[mid])
   high = mid - 1;
else if (x < v[mid])
   low = mid + 1;
else
   return mid;
```

```
if (x < v[mid])
    high = mid - 1;
else if (x > v[mid])
    low = mid + 1;
else
    return mid;
```

## Conventions

- Follow consistent naming style
  - use descriptive names for globals and functions
    e.g., **`WriteStrings, iMaxIterations, pcFilename`**
  - use concise names for local variables
    e.g., **`i`** (not **`arrayindex`**) for loop variable
  - use case judiciously
    e.g., **`PI`**, **`MAX_STRINGS`** (reserve for constants)
  - use consistent style for compound names
    e.g., **`writestrings`**, **`WriteStrings`**, **`write_strings`**

## Documentation

- Documentation
  - comments should add new information
    **`i = i + 1;  /* add one to i */`**
  - comments must agree with the code
  - comment procedural interfaces liberally
  - comment sections of code, not lines of code
  - master the language and its idioms; let the code speak for itself

## Example: Command Line Parsing

```
/***************************************/
/* Parse command line arguments        */
/* Input is argc and argv from main    */
/* Return 1 for success, 0 for failure */
/***************************************/

int ParseArguments(int argc, char **argv)
{
  /* Skip over program name */
  argc--; argv++;

  /* Loop through parsing command line arguments */
  while (argc > 0) {
    if (!strcmp(*argv, "-file")) { argv++; argc--; pcFilename = *argv; }
    else if (!strcmp(*argv, "-int")) { argv++; argc--; iArg = atoi(*argv); }
    else if (!strcmp(*argv, "-double")) { argv++; argc--; dArg = atof(*argv); }
    else if (!strcmp(*argv, "-flag")) { iFlag = 1; }
    else {
      fprintf(stderr, "Unrecognized recognized command line argument: %s\n", *argv);
      Usage();
      return 0;
    }
    argv++; argc--;
  }

  /* Return success */
  return 1;
}
```

## Scope

- The scope of an identifier says where it can be used

**stringarray.h**

```
extern void ReadStrings(char **strings, int *nstrings, int maxstrings, FILE *fp);
extern void WriteStrings(char **strings, int nstrings, FILE *fp);
extern void SortStrings(char **strings, int nstrings);
```

**sort.c**

```
#include "stringarray.h"

#define MAX_STRINGS 128

int main()
{
  char *strings[MAX_STRINGS];
  int nstrings;

  ReadStrings(strings, &nstrings, MAX_STRINGS, stdin);
  SortStrings(strings, nstrings);
  WriteStrings(strings, nstrings, stdout);

  return 0;
}
```

## Definitions and Declarations

- A declaration announces the properties of an identifier and adds it to current scope

```
extern int nstrings;
extern char **strings;
extern void WriteStrings(char **strings, int nstrings);
```

- A definition declares the identifier and causes storage to be allocated for it

```
int nstrings = 0;
char *strings[128];
void WriteStrings(char **strings, int nstrings)
{
  …
}
```

## Global Variables

- Functions can use global variables declared outside and above them

```
int stack[100];

int main() {
   . . .          <-- stack is in scope
}

int sp;

void push(int x) {
   . . .          <-- stack, sp is in scope
}
```

## Local Variables & Parameters

- Functions can declare and define local variables
  - created upon entry to the function
  - destroyed upon return
- Function parameters behave like initialized local variables
  - values copied into "local variables"

```
int CompareStrings(char *s1, char *s2)
{
  char *p1 = s1;
  char *p2 = s2;

  while (*p1 && *p2) {
    if (*p1 < *p2) return -1;
    else if (*p1 > *p2) return 1;
    p1++;
    p2++;
  }

  return 0;
}
```

```
int CompareStrings(char *s1, char *s2)
{
  while (*s1 && *s2) {
    if (*s1 < *s2) return -1;
    else if (*s1 > *s2) return 1;
    s1++;
    s2++;
  }

  return 0;
}
```

## Local Variables & Parameters

- Function parameters are transmitted by value
  - values copied into "local variables"
  - use pointers to pass variables "by reference"

```
void swap(int x, int  y)
{
   int t;

   t = x;
   x = y;
   y = t;
}
```

No!

```
void swap(int *x, int  *y)
{
   int t;

   t = *x;
   *x = *y;
   *y = t;
}
```

Yes

## Local Variables & Parameters

- Function parameters and local declarations "hide" outer-level declarations

```
int x, y;

. . .

f(int x, int a) {
     int b;
     . . .
     y = x + a*b;
     if (. . .) {
          int a;
          . . .
          y = x + a*b;
     }
}
```

## Local Variables & Parameters

- Cannot declare the same variable twice in one scope

```
f(int x) {
    int x;          <-- error!
    . . .
}
```

## Scope Example

```
int a, b;

main (void) {
    a = 1; b = 2;
    f(a);
    print(a, b);
}

void f(int a) {
    a = 3;
    {
        int b = 4;
        print(a, b);
    }
    print(a, b);
    b = 5;
}
```

Output

3 4
3 2
1 5

## Scope and Programming Style

- Avoid using same names for different purposes
  - Use different naming conventions for globals and locals
  - Avoid changing function arguments
- Use function parameters rather than global variables
  - Avoids misunderstood dependencies
  - Enables well-documented module interfaces
  - Allows code to be re-entrant (recursive, parallelizable)
- Declare variables in smallest scope possible
  - Allows other programmers to find declarations more easily
  - Minimizes dependencies between different sections of code

## Summary

- Programming style is important for good code
  - Structure
  - Conventions
  - Documentation
  - Scope
- Benefits of good programming style
  - Improves readability
  - Simplifies debugging
  - Simplifies maintenance
  - May improve re-use
  - etc.