Remote Procedure Call

Outline
- Protocol Stack
- Presentation Formatting

RPC Timeline



RCP Components

- Protocol Stack
  - BLAST: fragments and reassembles large messages
  - CHAN: synchronizes request and reply messages
  - SELECT: dispatches request to the correct process
- Stubs



Bulk Transfer (BLAST)

- Unlike AAL and IP, tries to recover from lost fragments
- Strategy
  - selective retransmission
  - aka partial acknowledgements



BLAST Details

- Sender:
  - after sending all fragments, set timer DONE
  - if receive SRR, send missing fragments and reset DONE
  - if timer DONE expires, free fragments

BLAST Details (cont)

- Receiver:
  - when first fragments arrives, set timer LAST_FRAG
  - when all fragments present, reassemble and pass up
  - four exceptional conditions:
    - if last fragment arrives but message not complete
      - send SRR and set timer RETRY
    - if timer LAST_FRAG expires
      - send SRR and set timer RETRY
    - if timer RETRY expires for first or second time
      - send SRR and set timer RETRY
    - if timer RETRY expires a third time
      - give up and free partial message

BLAST Header Format

- MID must protect against wrap around
- TYPE = DATA or SRR
- NumFrags indicates number of fragments
- FragMask distinguishes among fragments
  - if Type=DATA, identifies this fragment
  - if Type=SRR, identifies missing fragments



Request/Reply (CHAN)

- Guarantees message delivery
- Synchronizes client with server
- Supports *at-most-once* semantics

Simple case



Implicit Acks



CHAN Details

- Lost message (request, reply, or ACK)
  - set RETRANSMIT timer
  - use message id (MID) field to distinguish
- Slow (long running) server
  - client periodically sends “are you alive” probe, or
  - server periodically sends “I’m alive” notice
- Want to support multiple outstanding calls
  - use channel id (CID) field to distinguish
- Machines crash and reboot
  - use boot id (BID) field to distinguish

CHAN Header Format

```
typedef struct {
   u_short  Type;    /* REQ, REP, ACK, PROBE */
   u_short  CID;     /* unique channel id */
   int      MID;     /* unique message id */
   int      BID;     /* unique boot id */
   int      Length;  /* length of message */
   int      ProtNum; /* high-level protocol */
} ChanHdr;

typedef struct {
   u_char    type;         /* CLIENT or SERVER */
   u_char    status;       /* BUSY or IDLE */
   int       retries;      /* number of retries */
   int       timeout;      /* timeout value */
   XkReturn  ret_val;      /* return value */
   Msg       *request;     /* request message */
   Msg       *reply;       /* reply message */
   Semaphore reply_sem;    /* client semaphore */
   int       mid;          /* message id */
   int       bid;          /* boot id */
} ChanState;
```


Synchronous vs Asynchronous Protocols

- Asynchronous interface
  ```
  send(Protocol llp, Msg *message)
  deliver(Protocol llp, Msg *message)
  ```
- Synchronous interface
  ```
  call(Protocol llp, Msg *request, Msg *reply)
  upcall(Protocol hlp, Msg *request, Msg *reply)
  ```
- CHAN is a hybrid protocol
  - synchronous from above: **`call`**
  - asynchronous from below: **`deliver`**

Dispatcher (SELECT)

- Dispatch to appropriate procedure
- Synchronous counterpart to UDP
- Implement concurrency (open multiple CHANs)



- Address Space for Procedures
  - flat: unique id for each possible procedure
  - hierarchical: program + procedure number

Simple RPC Stack



SunRPC

- IP implements BLAST-equivalent
  - except no selective retransmit
- SunRPC implements CHAN-equivalent
  - except not at-most-once



- UDP + SunRPC implement SELECT-equivalent
  - UDP dispatches to program (ports bound to programs)
  - SunRPC dispatches to procedure within program

SunRPC Header Format

- XID (transaction id) is similar to CHAN's MID
- Server does not remember last XID it serviced
- Problem if client retransmits request while reply is in transit



Presentation Formatting

- Marshalling (encoding) application data into messages
- Unmarshalling (decoding) messages into application data

- Data types we consider
  - integers
  - floats
  - strings
  - arrays
  - structs
- Types of data we do not consider
  - images
  - video
  - multimedia documents

Difficulties

- Representation of base types
  - floating point: IEEE 754 versus non-standard
  - integer: big-endian versus little-endian (e.g., 34,677,374)



- Compiler layout of structures

Taxonomy

- Data types
  - base types (e.g., ints, floats); must convert
  - flat types (e.g., structures, arrays); must pack
  - complex types (e.g., pointers); must linearize



- Conversion Strategy
  - canonical intermediate form
  - receiver-makes-right (an *N* x *N* solution)

Taxonomy (cont)

- Tagged versus untagged data



- Stubs
  - compiled
  - interpreted



eXternal Data Representation (XDR)

- Defined by Sun for use with SunRPC
- C type system (without function pointers)
- Canonical intermediate form
- Untagged (except array length)
- Compiled stubs


```
#define MAXNAME 256;
#define MAXLIST 100;

struct item {
   int     count;
   char    name[MAXNAME];
   int     list[MAXLIST];
};

bool_t
xdr_item(XDR *xdrs, struct item *ptr)
{
   return(xdr_int(xdrs, &ptr->count) &&
        xdr_string(xdrs, &ptr->name, MAXNAME) &&
        xdr_array(xdrs, &ptr->list, &ptr->count,
                MAXLIST, sizeof(int), xdr_int));
}
```



Abstract Syntax Notation One (ASN-1)

- An ISO standard
- Essentially the C type system
- Canonical intermediate form
- Tagged
- Compiled or interpretted stubs
- BER: Basic Encoding Rules

(tag, length, value)



Network Data Representation (NDR)

- Defined by DCE
- Essentially the C type system
- Receiver-makes-right (architecture tag)
- Individual data items untagged
- Compiled stubs from IDL
- 4-byte architecture tag

– IntegerRep
  - 0 = big-endian
  - 1 = little-endian

– CharRep
  - 0 = ASCII
  - 1 = EBCDIC

– FloatRep
  - 0 = IEEE 754
  - 1 = VAX
  - 2 = Cray
  - 3 = IBM