

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

```
% gcc217 testforkloop.c -o testforkloop
```

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

% ./testforkloop

```
9857

int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {   for (i = 0; i < 10; i++)
        printf("%d child %d\n",
               (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

```
% ./testforkloop
```

```
9857

int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {
        for (i = 0; i < 10; i++)
            printf("%d child %d\n",
                   (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

% ./testforkloop

```
9857

int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {   for (i = 0; i < 10; i++)
        printf("%d child %d\n",
               (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

% ./testforkloop

```
9857

int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {   for (i = 0; i < 10; i++)
        printf("%d child %d\n",
               (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

Writes:

9857 parent

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

% ./testforkloop

```
9857

int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {   for (i = 0; i < 10; i++)
        printf("%d child %d\n",
               (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

% ./testforkloop

9857

```
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {
        for (i = 0; i < 10; i++)
            printf("%d child %d\n",
                   (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

9858

```
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {
        for (i = 0; i < 10; i++)
            printf("%d child %d\n",
                   (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

concurrent

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

% ./testforkloop

```
9857
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {
        for (i = 0; i < 10; i++)
            printf("%d child %d\n",
                   (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

```
9858
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {
        for (i = 0; i < 10; i++)
            printf("%d child %d\n",
                   (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

concurrent

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

% ./testforkloop

```
9857
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {   for (i = 0; i < 10; i++)
        printf("%d child %d\n",
               (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

```
9858
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {   for (i = 0; i < 10; i++)
        printf("%d child %d\n",
               (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

concurrent

Assume OS gives CPU to parent

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

% ./testforkloop

```
9857
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork(); 9858
    if (iPid == 0)
    {   for (i = 0; i < 10; i++)
        printf("%d child %d\n",
               (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

concurrent

```
9858
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork(); 9857
    if (iPid == 0)
    {   for (i = 0; i < 10; i++)
        printf("%d child %d\n",
               (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

Writes:

9857 parent 0 ... 7

10

Assume OS gives CPU to child

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

% ./testforkloop

```
9857
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {   for (i = 0; i < 10; i++)
        printf("%d child %d\n",
               (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

concurrent

```
9858
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {   for (i = 0; i < 10; i++)
        printf("%d child %d\n",
               (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

% ./testforkloop

```
9857

int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {   for (i = 0; i < 10; i++)
        printf("%d child %d\n",
               (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

concurrent

```
9858

int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
if (iPid == 0)
{   for (i = 0; i < 10; i++)
    printf("%d child %d\n",
           (int)getPid(), i);
    exit(0);
}
for (i = 0; i < 10; i++)
    printf("%d parent %d\n",
           (int)getPid(), i);
return 0;
}
```

Princeton University
 COS 217: Introduction to Programming Systems
 Trace of testforkloop

% ./testforkloop

```

9857

int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {
        for (i = 0; i < 10; i++)
            printf("%d child %d\n",
                   (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
    
```

concurrent

```

9858

int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {
        for (i = 0; i < 10; i++)
            printf("%d child %d\n",
                   (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
    
```

Writes:

9858 child 0

13

Assume OS gives CPU to parent

Princeton University
 COS 217: Introduction to Programming Systems
 Trace of testforkloop

% ./testforkloop

```
9857
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork(); 9858
    if (iPid == 0)
    {   for (i = 0; i < 10; i++)
        printf("%d child %d\n",
               (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

concurrent

```
9858
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid()); 0
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {   for (i = 0; i < 10; i++)
        printf("%d child %d\n",
               (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

Writes:

9857 parent 8

14

Assume OS gives CPU to child

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

% ./testforkloop

```
9857

int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {
        for (i = 0; i < 10; i++)
            printf("%d child %d\n",
                   (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

concurrent

```
9858

int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {
        for (i = 0; i < 10; i++)
            printf("%d child %d\n",
                   (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

Writes:

9858 child 1

15

Assume OS gives CPU to parent

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

% ./testforkloop

```
9857
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {   for (i = 0; i < 10; i++)
        printf("%d child %d\n",
               (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

concurrent

```
9858
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {   for (i = 0; i < 10; i++)
        printf("%d child %d\n",
               (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

Writes:

9857 parent 9

16

Assume OS gives CPU to parent

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

% ./testforkloop

```
9857
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {
        for (i = 0; i < 10; i++)
            printf("%d child %d\n",
                   (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

concurrent

```
9858
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {
        for (i = 0; i < 10; i++)
            printf("%d child %d\n",
                   (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

% ./testforkloop

```
9858
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int)getPid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {
        for (i = 0; i < 10; i++)
            printf("%d child %d\n",
                   (int)getPid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n",
               (int)getPid(), i);
    return 0;
}
```

Writes:

9858 child 2 ... 9

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

% ./testforkloop

```
1858
int main(void)
{
    pid_t iPid;
    int i;
    printf("%d parent\n",
           (int) getpid());
    fflush(NULL);
    iPid = fork();
    if (iPid == 0)
    {
        for (i = 0; i < 10; i++)
            printf("%d child %d\n",
                   (int) getpid(), i);
        exit(0);
    }
    for (i = 0; i < 10; i++)
        printf("%d parent %d\n"
               (int) getpid(), i);
    return 0;
```

Princeton University
COS 217: Introduction to Programming Systems
Trace of testforkloop

%

Copyright © 2016 by Robert M. Dondero, Jr.