Macro Example

- int max (int c, int a, int b) { vs . **#define** *max(c,a,b) (c = ((a>b) ? a:b))*

  c = (a>b) ? return a : return b;

  }

- int main () {

  int x=3,y=5,z=0;

  max (z,x++,y++);

  printf (“max of x=%d and y=%d is %d\n”, x,y,z);

  }

Copyright ©1995 D. Hanson, K. Li & J.P. Singh

Make

- Typical program development cycle



- Potential problems

  edit a file, but forget to compile it

  edit an interface, but forget to compile ***all*** the files that ***depend*** on it

  do more compilation than is necessary

- **`make`** ***automates*** compiling and building a program



Copyright ©1995 D. Hanson, K. Li & J.P. Singh

Dependency Graphs

- make processes a ***dependency graph***



  each node represents a ***file***

  each node is annotated with the ***command*** that "makes" the file

- To make node *X*

  make all dependents of *X* (those ***modified more recently*** than *X*)

  update *X* using the associated command

  if **`strset.h`** or **`main.c`** is newer than **`main.o`**

  re-make **`main.o`** with "**`lcc -c main.c`**"

Copyright ©1995 D. Hanson, K. Li & J.P. Singh

Makefiles

- **`makefile`** or **`Makefile`** **specifies the dependency graph of make**

  targets: dependents
  commands

```
unique:     main.o strset.o
            lcc -o unique main.o strset.o

main.o:     main.c strset.h
            lcc -c main.c

strset.o:   strset.c strset.h
            lcc -c strset.c
```

- To invoke **`make`**

  `make` ***targets*** ...

```
make strset.o
make unique
```

- With no arguments, **`make`** makes the ***first*** target listed in **`makefile`**

```
% make
lcc -c main.c
lcc -c strset.c
lcc -o unique main.o strset.o
```

```
% touch strset.c
% make strset.o
lcc -c strset.c
% make
lcc -o unique main.o strset.o
```

Copyright ©1995 D. Hanson, K. Li & J.P. Singh

Built-ins and Macros

- **make** contains ***built-in*** dependencies and commands

  a "**.o**" file is assumed from a "**.c**" file by the C compiler

```
unique:      main.o strset.o
             lcc -o unique main.o strset.o

main.o strset.o: strset.h
```

- **make** has a simple ***macro*** facility; macros communicate with built-in commands and simplify **makefile**s

```
CC=lcc -A
CFLAGS=-g
LDFLAGS=-g
STRSET=strset0
OBJS=main.o $(STRSET).o

a.out: $(OBJS)
       $(CC) $(LDFLAGS) $(OBJS)

$(OBJS): strset.h
```

```
% make -n
lcc -A -g -c main.c
lcc -A -g -c strset0.c
lcc -A -g main.o strset0.o
% make -n STRSET=strset1
lcc -A -g -c main.c
lcc -A -g -c strset1.c
lcc -A -g main.o strset1.o
% setenv STRSET strset1
% make -e
lcc -A -g -c main.c
lcc -A -g -c strset1.c
lcc -A -g main.o strset1.o
%
```

Copyright ©1995 D. Hanson, K. Li & J.P. Singh

Dummy Targets, Prefixes, and Built-in Macros

- "Dummy" targets for common command sequences

```
install: a.out
        cp a.out unique
        strip unique

clean:
        -rm *.o core

clobber: clean
        rm -f a.out unique
```

"–" prefix ignores errors

make clean removes "**.o**" and **core** files

- Dummy targets can be created if only for their modification time

```
FILES=main.c strset.h strset0 strset1.c
...
print:  $(FILES)
        @enscript $?
        @touch print
```

$? macro expands into "younger" dependents

"@" prefix suppresses command echoing

- Use dummy targets for all "program maintenance" tasks

clean	**install**	**print**
release	**submit**	**test**

- **Don't *overuse* dummy targets and macros**

Copyright ©1995 D. Hanson, K. Li & J.P. Singh

Version-Control Tools

- Software systems ***evolve*** — they advance in steps or ***versions***
  - repair bugs
  - add performance improvements and new features
  - add versions for other platforms (SPARC, ALPHA, x86, ...)
- Might have to retrieve ***old*** versions
- ***Version-control*** tools help maintain versions of programs, or any files
- ***Revision trees***



Copyright ©1995 D. Hanson, K. Li & J.P. Singh

Why Revision Control

- Store and retrieve multiple versions of a file
- Maintain a history and log of changes
- Resolve access conflicts
- Maintain a tree with separate paths
  - can merge paths as well
- Control releases and their status
- Reduce storage

Copyright ©1995 D. Hanson, K. Li & J.P. Singh

Revision Control System

- "Checking in" a file creates a new version, including the initial version

  `ci main.c`

  creates the version file **`main.c,v`** that holds **`main.c`** as version 1.1

  deletes **`main.c`**

- "Checking out" a file retrieves a copy of the latest version

  `co main.c` checks out a ***read-only*** copy
  `lcc -c main.c`

  `co -l main.c` checks out a ***read/write*** copy, ***locks*** **`main.c,v`**
  `emacs main.c`
  `lcc -c main.c`
  `ci main.c` checks in new **`main.c`** as version 1.2

- Options specify explicit versions for **`co`** and **`ci`**

  `co -r1.2 main.c` checks out a read-only copy of version 1.2 **`main.c`**
  `co -l1.2 main.c` checks out a read/write copy of version 1.2 **`main.c`**
  `ci -r2 main.c` checks in a new "release" of **`main.c`**

Copyright ©1995 D. Hanson, K. Li & J.P. Singh

Branching

- Branching occurs to fix bugs, enhance old versions, ...
-


```
ci main.c
co -l main.c; emacs; ... ; ci main.c
```




```
co -l main.c; emacs; ... ; ci main.c
```




```
co -l main.c; emacs; ... ; ci -r2 main.c
```




```
co -l main.c; emacs; ... ; ci main.c
```



- What if you would like to fix and enhance version 1.3?

Copyright ©1995 D. Hanson, K. Li & J.P. Singh

Branching, cont'd

- Create a ***branch*** at version 1.3

```
co -l1.3 main.c; emacs; ... ; ci -r1.3.1 main.c
```



- Extra revision number in 1.3.1.***1*** allows for subsequent revisions

```
co -l1.3.1 main.c; emacs; ... ; ci -r1.3.1 main.c
```



- See RCS man pages for information on more options, commands, ...

Copyright ©1995 D. Hanson, K. Li & J.P. Singh

Using RCS with Make

- Using RCS with **make**

  ***.c** depends on ***.c,v**

```
main.c:     main.c,v
            co main.c
```

  RCS automatically looks in the directory **RCS** for **,v** files

```
main.c:     RCS/main.c,v
            co main.c
```

  "**make clobber**" should remove **.c** files

```
clobber:    clean
            rm -f wf main.c parse.c table.c
```

  or, if **rcsclean** is available

```
clobber:    clean
            rm -f wf; rcsclean *.[ch]
```

- **Revised program development cycle**



Copyright ©1995 D. Hanson, K. Li & J.P. Singh

RCS Implementation

- Revisions are stored in the version file in ***differential form***

  if **`main.c`** has the revision tree



  `main.c,v` holds all of version 1.3
  edit script to convert 1.3 to 1.2
  edit script to convert 1.2 to 1.1

- RCS revisions are ***backward deltas*** . Why?
- Other systems,such as SCCS use ***forward deltas***

  version file holds all of version 1.1
  edit script to convert 1.1 to 1.2
  edit script to convert 1.2 to 1.3

- Deltas are computed with ***"diff"***

  `diff -e main.old main.c`

  generates **`ed`** commands to edit **`main.old`** into **`main.c`**

  see Section 5.9 in Kernighan and Pike, The UNIX Programming Environment

Copyright ©1995 D. Hanson, K. Li & J.P. Singh